

AUDIO

WISPEAK WIRELESS PRO AUDIO	2
TRANSMITTER	2
RECEIVERS	2
ACCESSORIES	3
SOUND SOURCES	3
MICROPHONES	3
AUDIO PLAYERS	3
INSTALLATION MIXERS	4
INSTALLATION MIXERS	4
DIGITAL MATRIXES & PROCESSORS	5
DIGITAL MATRIXES	5
DIGITAL ZONERS	6
DANTE INTERFACES	6
LOUDSPEAKERS PROCESSORS	6
AMPLIFIERS	6
NETWORKABLE AMPLIFIERS	6
COMMERCIAL AMPLIFIERS	8
MIXING AMPLIFIERS	10
ULTRA COMPACT AMPLIFIERS	11
LOUDSPEAKERS	11
IN-CEILING LOUDSPEAKERS	11
HIGH PERFORMANCE LOUDSPEAKERS	13
COMMERCIAL LOUDSPEAKERS	18
SUBWOOFERS	21
INDUSTRIAL LOUDPEAKERS	23
REMOTE CONTROLS & INTERFACES	23
PAGING STATIONS	23
DIGITAL CONTROLS & PANELS	24
ANALOGUE CONTROLS & PANELS	25
ACCESSORIES	26
PRODUCT ACCESSORIES	26
AUDIO CABLES & OTHERS	27
LOUDSPEAKERS HARDWARE	29

VIDEO


SWITCHERS	32
MATRIXES	33
SPLITTERS	34
VIDEO DISTRIBUTION OVER IP	34
EXTENDERS	35
AUDIO MANAGEMENT DEVICES	35
AV INTERFACES	36
ACCESSORIES	36

* RRP: Recommended Retail Price.









AUDIO

WISPEAK WIRELESS PRO AUDIO



TRANSMITTER

Ref.	Name		Lista ár HUF	RRP €
CCORE	CORE	 <p>WISPEAK CORE is the transmitter device that communicates with all the receiver devices to create a WISPEAK wireless network, and takes the role of the Master Unit. Its main functions are to pair and send audio contents to all the receivers. Includes 3 audio inputs (Euroblock, RCA, Bluetooth), remote port for a WPA-VOL panel and a MUTE port for external dry contact triggering. Managed by WISPEAK grip app. Dimensions 225x120x40mm / 8.9"x4.7"x1.6". Weight 0.8kg / 1.76 lb.</p>	197,620 Ft	482 €

RECEIVERS





Ref.	Name		Lista ár HUF	RRP €
CTUBE3WH	TUBE	 <p>WISPEAK TUBE is a self-powered 3" lamp style loudspeaker with wireless audio reception and control capabilities under the control of the Master unit, featuring an AUX output (Euroblock) and an installation system which is compatible with ceiling light rails. Dimensions (without accessories) Ø 96mm x 110mm / Ø 3,8" x 4,3" . Weight 0,8 kg / 1.76lb. White colour. Delivered by units. Price per unit.</p>	160,720 Ft	392 €
CTUBE3BK	TUBE	 <p>WISPEAK TUBE is a self-powered 3" lamp style loudspeaker with wireless audio reception and control capabilities under the control of the Master unit, featuring an AUX output (Euroblock) and an installation system which is compatible with ceiling light rails. Dimensions (without accessories) Ø 96mm x 110mm / Ø 3,8" x 4,3" . Weight 0,8 kg / 1.76lb. Black colour. Delivered by units. Price per unit.</p>	160,720 Ft	392 €
CCUBE5WH	CUBE	 <p>WISPEAK CUBE is a self-powered 5" loudspeaker cabinet with wireless audio reception and control capabilities under the control of the Master unit, featuring an AUX output (Euroblock) and an installation system which is compatible with ceiling light rails. Alternatively, wall mount or desktop installation is as well possible by means of the included accessories. Dimensions (without accessories) 173x180x185 mm / 6,81" x 7,08" x 7,28". Weight 2,4kg / 5.29lb. White colour. Delivered by units. Price per unit.</p>	202,540 Ft	494 €
CCUBE5BK	CUBE	 <p>WISPEAK CUBE is a self-powered 5" loudspeaker cabinet with wireless audio reception and control capabilities under the control of the Master unit, featuring an AUX output (Euroblock) and an installation system which is compatible with ceiling light rails. Alternatively, wall mount or desktop installation is as well possible by means of the included accessories. Dimensions (without accessories) 173x180x185 mm / 6,81" x 7,08" x 7,28". Weight 2,4kg / 5.29lb. Black colour. Delivered by units. Price per unit.</p>	202,540 Ft	494 €
CGLOBESPDWH	GLOBE	 <p>WISPEAK GLOBE is a self-powered 2-way full range sphere loudspeaker cabinet with wireless audio reception and control capabilities under the control of a WISPEAK CORE Master unit, featuring a pendant installation system. Includes a 5" woofer and a 1" silk dome tweeter. Dimensions (without accessories) Ø287mm x 331mm(H) / Ø11.3 in. x 13 in. (H). Weight 2.2 Kg / 4.85 lbs. White colour. Delivered by units. Price per unit.</p>	191,470 Ft	467 €
CGLOBESPDBK	GLOBE	 <p>WISPEAK GLOBE is a self-powered 2-way full range sphere loudspeaker cabinet with wireless audio reception and control capabilities under the control of a WISPEAK CORE Master unit, featuring a pendant installation system. Includes a 5" woofer and a 1" silk dome tweeter. Dimensions (without accessories) Ø287mm x 331mm(H) / Ø11.3 in. x 13 in. (H). Weight 2.2 Kg / 4.85 lbs. Black colour. Delivered by units. Price per unit.</p>	191,552 Ft	467 €
CGLOBESRMWH	GLOBE	 <p>WISPEAK GLOBE is a self-powered 2-way full range sphere loudspeaker cabinet with wireless audio reception and control capabilities under the control of a WISPEAK CORE Master unit, featuring an installation system which is compatible with ceiling light rails. Includes a 5" woofer and a 1" silk dome tweeter. Dimensions (without accessories) Ø287mm x 331mm(H) / Ø11.3 in. x 13 in. (H). Weight 2.2 Kg / 4.85 lbs. White colour. Delivered by units. Price per unit.</p>	191,470 Ft	467 €
CGLOBESRMBK	GLOBE	 <p>WISPEAK GLOBE is a self-powered 2-way full range sphere loudspeaker cabinet with wireless audio reception and control capabilities under the control of a WISPEAK CORE Master unit, featuring an installation system which is compatible with ceiling light rails. Includes a 5" woofer and a 1" silk dome tweeter. Dimensions (without accessories) Ø287mm x 331mm(H) / Ø11.3 in. x 13 in. (H). Weight 2.2 Kg / 4.85 lbs. Black colour. Delivered by units. Price per unit.</p>	191,470 Ft	467 €

ACCESSORIES





Ref.	Name		Lista ár HUF	RRP €
CTUBESMAWH	TUBE SMA	TUBESMA is a surface mount adapter to allow installing a TUBE unit in locations where there is no available lighting rail.	15,580 Ft	38 €
				
CTUBESMABK	TUBE SMA	TUBESMA is a surface mount adapter to allow installing a TUBE unit in locations where there is no available lighting rail.	15,580 Ft	38 €
				

SOUND SOURCES

MICROPHONES

Ref.	Name		Lista ár HUF	RRP €
CEMHH1	eMHH1	Affordable handheld cardioid dynamic microphone, with a robust design that makes it ideal for voice applications. It comes with a microphone stand adapter, 6 metres XLR-XLR cable and transport bag. Dimensions 185 x 50 x 50 mm. Weight 246 g.	27,060 Ft	66 €
				
CEMCN2	eMCN2	Condenser gooseneck cardioid microphone, with a perfect profile for message, speech and conferencing applications. Total length 55 cm. It includes anti-pop wind-screen cover.	45,920 Ft	112 €
				
CEMBASE	eMBASE	Desktop connection base for the eMCN2 microphone, as well as for other microphones with standard XLR connector. It includes ON / OFF switch that enables / disables the microphone signal. Dimensions 45 x 140 x 110 mm. Weight: 860g.	34,850 Ft	85 €
				
CEMICFIT2	eMICFIT2	eMICFIT2 is a robust headset condenser microphone, including a water and sweat resistant treatment, ideal for sport and fitness applications. It performs an easy adjustment of the gooseneck and a discrete, light and comfortable design in combination with a robust and solid body. It features a mini-XLR 4-pin connector, compatible with the eMWE UHF wireless belt-pack unit. It includes anti-pop wind-screen cover and rigid case. Dimensions Ø 9.7 x 4.5mm / Ø 0.38" x 0.18". Weight 52 g / 0.11 lb.	54,120 Ft	132 €
				

AUDIO PLAYERS

Ref.	Name		Lista ár HUF	RRP €
CPLAYERONE	PLAYER ONE	Compact audio player with a stereo output that can play music contents from local storage media (USB/MicroSD card), Internet streams or digital sharing streams (DLNA and Airplay compatible). It includes Ethernet port, WiFi connection, USB and Micro-SD reader slots, front panel LCD display and local controls .Remote management by Ecler GALLERY, remote control by RePLAYER mobile app. Dimensions 241 x 44 x 152mm (install 2 PLAYER ONE in 1RU with 1UHRMKIT accessory). Weight 680 g.	201,720 Ft	492 €
				
CPLAYERZERO	PLAYER ZERO	Compact audio player with a stereo output that can play music contents from local storage media (USB/MicroSD card), Internet streams or digital sharing streams (DLNA and Airplay compatible). It includes Ethernet port, WiFi connection, USB and Micro-SD reader slots .Remote management by Ecler GALLERY, remote control by RePLAYER mobile app. Dimensions 126.5 x 44 x 132 mm / 4.98" x 1.73" x 5.19". Weight 0.6 Kg / 1.32 lb	161,540 Ft	394 €
				
CDUONTPLAYER	DUONET PLAYER	Double audio sound source that features full EclerNet compatibility (UCP control system, WPNETTOUCH remote management, TP-NET protocol, etc.). It includes 2 independent stereo media players, each one being able to play Internet audio streams and local (USB/SD) or networked audio media. The device have 2 Euroblock line level balanced outputs, remote control, priority (messages, warnings) and 4 GPI ports to trigger events. Dimensions 482 x 44(1RU) x 250mm. Weight 4,2 kg	432,960 Ft	1,056 €
				
CESASBT	eSAS-BT	Stereo audio source including FM tuner, USB slot, SD slot and Bluetooth connection. It performs unbalanced and balanced stereo audio outputs and headphones output (jack) with volume control in frontal panel. IR remote control, FM antenna, 2x RCA cables and rack-mount bracket included. Dimensions 482 x 44(1RU) x 132mm. Weight 1,4 kg	110,700 Ft	270 €
				





INSTALLATION MIXERS

INSTALLATION MIXERS

Ref.	Name	SAM SERIES	Lista ár HUF	RRP €
EOL	CESAM402C eSAM402	Installation audio mixer in standard rack format, featuring 3 MIC/LINE ST inputs, 1 LINE ST input, 1 main mix balanced output and one AUX/REC additional output. It includes a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, 18V phantom power for all mic inputs, ST/MONO mix switch and MUTE port for external dry contact triggering. Dimensions 482.6 x 44(1RU) x 120 mm. Weight 1,7 kg	159,080 Ft	388 €
EOL	CESAM702C eSAM702	Installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs, 1 LINE ST input, 1 main mix balanced output and one AUX/REC additional output. It includes a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, 18V phantom available for all mic inputs, ST/MONO mix switch and MUTE port for external dry contact triggering. Dimensions 482.6 x 44(1RU) x 120 mm. Weight 1,8 kg	210,330 Ft	513 €
EOL	CESAM603C eSAM603	6 inputs and 3 outputs installation audio mixer. Inputs: 1x MIC, 4x MIC/LINE ST, 1x LINE ST. Outputs: 1x ST (A/B) and 1x MONO (C). A/B output can operate in ST/MONO mode. Each input can be routed to output A, B and/or C. It includes a 3 band tone control section, talkover (priority) function assignable to each input over the mix bus, ST/MONO mix switch for A/B output and MUTE port for external dry contact triggering. Dimensions 482.6x44(1RU)x120 mm. Weight 2,1 kg	218,940 Ft	534 €







EOL	CSAM612T SAM612T	Installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs + 1 ST MIX input and 1 stereo balanced output. Each input has a dedicated 3-band tone control and 18V phantom power for MIC inputs. Input 1 includes talkover (priority) function over the mix bus and additional front panel jack connector. Main output ST/MONO mode switch and MUTE port for external dry contact triggering. Dimensions 482.6x44(1RU)x120 mm. Weight 2,0 kg	242,720 Ft	592 €
-----	----------------------------------	--	------------	-------

Ref.	Name	COMPACT SERIES	Lista ár HUF	RRP €
	CECOMPACT4BT eCOMPACT4BT	Desktop/19" rack installation mixer. INS: 4 mic with switchable HP-filter and Phantom power 48V; 6 line ST; Bluetooth® connex; aux (mini-jack). OUTS: main balanced (XLR) with ST/mono switch; SUB OUT mono (XLR) with switchable LP-filter; alternative ALT (RCA); headphones (mini-Jack). 3 Band tone Ctrl and ALT OUT (alternative output) send per channel on all channels; Talkover (CH4) with mic input (combo) and USB charging port. It includes power supply and rack-mount kit.	357,520 Ft	872 €



Ref.	Name	SAMI SERIES	Lista ár HUF	RRP €
NEW!	CSAMI402 SAMI-402	Installation audio mixer in standard rack format, featuring 3 MIC/LINE ST inputs, 1 LINE ST input, 1 main mix balanced output and one AUX/REC additional output. It includes a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, 18V phantom power for all mic inputs, ST/MONO mix switch and MUTE port for external dry contact triggering. Dimensions 482.6 x 44(1RU) x 120 mm. Weight 1,7 kg	159,080 Ft	388 €
	 Available in 2025			
NEW!	CSAMI702BT SAMI-702BT	Installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs, 1 BT input, 1 main mix balanced output and one AUX/REC additional output. It includes a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, 18V phantom available for all mic inputs, ST/MONO mix switch and MUTE port for external dry contact triggering. Dimensions 482.6 x 44(1RU) x 120 mm. Weight 1,8 kg	245,590 Ft	599 €
	 Available in 2025			
NEW!	CSAMI603 SAMI-603	6 inputs and 3 outputs installation audio mixer. Inputs: 1x MIC, 4x MIC/LINE ST, 1x LINE ST. Outputs: 1x ST (A/B) and 1x MONO (C). A/B output can operate in ST/MONO mode. Each input can be routed to output A, B and/or C. It includes a 3 band tone control section, talkover (priority) function assignable to each input over the mix bus, ST/MONO mix switch for A/B output and MUTE port for external dry contact triggering. Dimensions 482.6x44(1RU)x120 mm. Weight 2,1 kg	218,940 Ft	534 €
	 Available in 2025			
NEW!	CSAMI612 SAMI-612	Installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs + 1 ST MIX input and 1 stereo balanced output. Each input has a dedicated 3-band tone control and 18V phantom power for MIC inputs. Input 1 includes talkover (priority) function over the mix bus and additional front panel jack connector. Main output ST/MONO mode switch and MUTE port for external dry contact triggering. Dimensions 482.6x44(1RU)x120 mm. Weight 2,0 kg	225,090 Ft	549 €
	 Available in 2025			


DIGITAL MATRIXES & PROCESSORS



DIGITAL MATRIXES

Ref.	Name		Lista ár HUF	RRP €
CDAM614C	DAM614	Fully programmable audio digital mixer. It includes 6 audio inputs (2x LINE ST + 4x LINE/MIC being possible to use them independently (mono) or as stereo-coupled inputs) and 4 audio outputs (can be used as mono or stereo zones). Phantom power, front panel inputs and outputs level controls, DSP processing, RS-232 connectivity (compatible with EclerCOMM/CA-NET) and 4 REMOTE control ports (0-10VDC). Dimensions 482.6 x 44(1RU) x 120 mm. Weight 2.00 kg	378,430 Ft	923 €
				
Ref.	Name	MIMO Series	Lista ár HUF	RRP €
CMIMO7272DN	MIMO7272DN	64x64 native processing digital matrix with 72 inputs and 72 outputs (8 analogue inputs, 8 analogue outputs, 64 Dante™ inputs and 64 Dante™ outputs). Incorporating audio over IP technology, MIMO7272DN allows signal transmission using a Local Ethernet network. It features accessories from WPNET Series connected by Ethernet. MIMO7272DN is also capable of executing EclerNet projects thanks to its processor acting as a UCP server. Dimensions 482,6x44x266,5mm. Weight 3.25 kg	1,652,710 Ft	4,031 €
				
CMIMO4040CDN	MIMO4040CDN	Digital matrix with native processing of 40 inputs and 40 outputs (8 analogue inputs, 8 analogue outputs, 32 Dante™ inputs and 32 Dante™ outputs). MIMO4040CDN comes with a CONFERENCE tailored firmware, including Automixer, Feedback Killer and Acoustic Echo Cancelling functions. It features accessories from WPNET Series connected by Ethernet. MIMO4040CDN is also capable of executing EclerNet projects thanks to its processor acting as a UCP server. Dimensions 482,6x44x266,5mm. Weight 3.25 kg	1,652,710 Ft	4,031 €
				
CM40AEC2EXP	M40AEC2EXP	Expansion license +2 AEC processing channels for MIMO4040CDN *up to 8 AEC channels max. available in MIMO4040CDN	45,920 Ft	112 €
CM40AEC4EXP	M40AEC4EXP	Expansion license +4 AEC processing channels for MIMO4040CDN *up to 8 AEC channels max. available in MIMO4040CDN	92,250 Ft	225 €
CM40AEC6EXP	M40AEC6EXP	Expansion license +6 AEC processing channels for MIMO4040CDN *up to 8 AEC channels max. available in MIMO4040CDN	138,580 Ft	338 €
CMIMO88	MIMO88	8 balanced MIC/LINE inputs / 8 balanced outputs + 2 monitor outputs digital audio matrix, fully programmable through EclerNet Manager and linkable to a second unit to become a 16x16 matrix. Includes 8 GPI and 8 GPO ports. DSP processing: Parametric EQ & filters for each channel, delays, compressor/limiter, paging, priority, automatic mix (MIMO Firmware) and remote control via UCP or WPNETTOUCH. Dimensions 482.6 x 44 x 266.5 mm. Weight 3.5 kg	1,109,870 Ft	2,707 €
				
CMIMO88SG	MIMO88SG	8 balanced MIC/LINE inputs / 8 balanced outputs digital audio matrix, fully programmable through EclerNet Manager. Includes 8 GPI ports. DSP processing: Parametric EQ & filters for each channel, delays, compressor/limiter, paging, priority, automatic mix (MIMO Firmware) and remote control via UCP or WPNETTOUCH. Dimensions 482.6 x 44 x 266.5 mm. Weight 3.5 kg	719,960 Ft	1,756 €
				
CMIMO1212SG	MIMO1212SG	12 balanced MIC/LINE inputs / 12 balanced outputs digital audio matrix, fully programmable through EclerNet Manager. Includes 12 GPI ports. DSP processing: Parametric EQ & filters for each channel, delays, compressor/limiter, paging, priority, automatic mix (MIMO Firmware) and remote control via UCP or WPNETTOUCH. Dimensions 1RU x 266,5mm depth. Weight 3,5 kg	828,200 Ft	2,020 €
				

DIGITAL ZONERS




Ref.	Name	HUB Series	Lista ár HUF	RRP €
CHUB1408	HUB1408	HUB1408 is a digital audio zoner with a global size of 14 input and 8 output analogue channels. Available inputs are 4 MIC/LINE and 2 ST LINE local inputs, and 8 REMOTE LINE inputs. Available DSP: frequency shifter, link stereo, delay, crossover filters, graphic EQ, compressor/limiter and much more. Ecler pilot application, compatible with Android and iOS: control graphic panels set to user requirements. HxWxD: 88 (2RU) x 482,6 x 200mm. Weight 3,7 kg	488,720 Ft	1,192 €
				
CHUB1616	HUB1616	HUB1616 is a digital audio zoner with a global size of 16 input and 16 output analogue channels. The input channels are: 4 channels for MIC/MONO LINE, 4 channels for ST LINE and 8 channels for MONO LINE received on the unit's REMOTE ports, from wall panels eMCONTROL1. Available DSP: frequency shifter, link stereo, delay, crossover filters, graphic EQ, compressor/limiter and much more. Ecler pilot application, compatible with Android and iOS: control graphic panels set to user requirements. HxWxD: 88 (2RU) x 482,6 x 200mm. Weight 3,7 kg	658,460 Ft	1,606 €
				


DANTE INTERFACES				
Ref.	Name		Lista ár HUF	RRP €
CDN44BOBC	DN44BOB	 <p>4 inputs/4 outputs DANTE (Audio Over IP) Break Out Box. It allows to convert 4 analogue audio signals into 4 DANTE channels and send them into an Ethernet LAN, as well as to take 4 DANTE channels from the Ethernet network and convert them to analogue audio signals. It includes 4 GPI (0-10VDC) and 4 GPO control ports (NO/NC relays). Can be used together with EclerNet DANTE ready products or as a stand-alone DANTE interface. PUM3 included: rack-mount accessory to mount 2 halfwidth RU devices in 1 standard width RU space. Dimensions 241 x 44(1RU) x 152 mm. Weight 1.1 kg</p>	501,840 Ft	1,224 €

LOUDSPEAKERS PROCESSORS				
Ref.	Name	ALMA SERIES	Lista ár HUF	RRP €
CALMA24	ALMA24	 <p>Digital loudspeaker manager including 2 audio inputs and 4 audio outputs (all balanced), USB interface and 2 volume remote control ports (0-10VDC). Includes DSP processor 24bits/48kHz, parametric EQ, 3 crossover types, 20 user presets and password protection. ALMA24 is a 1RU stand-alone processor and EclerCOMM Manager compatibility. Dimensions 482.6 x 44 x 120 mm. Weight 1.75 kg</p>	257,480 Ft	628 €
CALMA26	ALMA26	 <p>Digital loudspeaker manager including 2 audio inputs and 6 audio outputs (all balanced), USB interface and 2 volume remote control ports (0-10VDC). Includes DSP processor 24bits/48kHz, parametric EQ, 3 crossover types, 20 user presets and password protection. ALMA24 is a 1RU stand-alone processor and EclerCOMM Manager compatibility. Dimensions 482.6 x 44 x 120 mm. Peso 1.75 kg</p>	351,780 Ft	858 €

AMPLIFIERS

NETWORKABLE AMPLIFIERS

Ref.	Name	VIDA SERIES	Lista ár HUF	RRP €
NEW! CVIDA16Q	VIDA-16Q	 <p>1600W digital amplifier, with 4 amplified outputs that can be independently configured in high (100/70V) or low (8/4/2ohm) impedance. The VersaPower technology, developed by Ecler, allows an asymmetrical power distribution. Max output power @ 2Ω/4Ω/8Ω or @70/100V - Single channel is 1600W. Audio player - with microSD slot for local audio files – as well as signal generator, plus 2 auxiliary line outputs and 4 Dante digital outputs. Internal matrix and signal processing. Remote control user application for iOS/Android/Web. Control and scheduled events for automation. Ultra low power consumption mode. Dimensions 482,6x88(2RU)x410 mm / 19"x3.46"x16.14". Weight 9,3 kg. / 20.5 lb.</p>	1,084,450 Ft	2,645 €
NEW! CVIDA24Q	VIDA-24Q	 <p>2400W digital amplifier, with 4 amplified outputs that can be independently configured in high (100/70V) or low (8/4/2ohm) impedance. Max output power @ 2Ω/4Ω/8Ω or @70/100V – 4x600W /4 Ω symmetrical power distribution. The VersaPower technology, developed by Ecler, allows an asymmetrical power distribution with a max output power @ 4Ω or 100V – into one single channel 2400W. Audio player - with microSD slot for local audio files – as well as signal generator, plus 2 auxiliary line outputs and 4 Dante digital outputs. Internal matrix and signal processing. Remote control user application for iOS/Android/Web. Control and scheduled events for automation. Ultra low power consumption mode. Dimensions 482,6x88(2RU)x410 mm / 19"x3.46"x16.14". Weight 9,3 kg. / 20.5 lb.</p>	1,228,770 Ft	2,997 €
NEW! CVIDA48Q	VIDA-48Q	 <p>4800W digital amplifier, with 4 amplified outputs that can be independently configured in high (100/70V) or low (8/4/2ohm) impedance. The VersaPower technology, developed by Ecler, allows an asymmetrical power distribution. Max output power @ 2Ω/4Ω/8Ω or @70/100V - Single channel is 4800W. Audio player - with microSD slot for local audio files – as well as signal generator, plus 2 auxiliary line outputs and 4 Dante digital outputs. Internal matrix and signal processing. Remote control user application for iOS/Android/Web. Control and scheduled events for automation. Ultra low power consumption mode. Dimensions 482,6x88(2RU)x410 mm / 19"x3.46"x16.14". Weight 9,3 kg. / 20.5 lb.</p>	1,473,950 Ft	3,595 €

Ref.	Name	Merchandising VIDA SERIES	Lista ár HUF	RRP €
NEW! CMCEVIDAS CMCEVIDAM CMCEVIDAL CMCEVIDAXL CMCEVIDAXXL	VIDA T-SHIRT	 <p>Imperial grey T-shirt VIDA Series Special Edition. Sizes: S, M, L, XL, XXL. Price per unit.</p>	7,790 Ft	19 €

Ref.	Name	HADA SERIES	Lista ár HUF	RRP €
NEW!	CHADA4B150	HADA-4B150	503,890 Ft	1,229 €
		HADA-4B150 is a 4x125W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 4.7 Kg / 10.36 lbs		
NEW!	CHADA4B250	HADA-4B250	544,890 Ft	1,329 €
		HADA-4B250 is a 4x250W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 5.0 Kg / 11.02 lb		
NEW!	CHADA4B400	HADA-4B400	594,090 Ft	1,449 €
		HADA-4B400 is a 4x400W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 5.4 Kg / 11.91 lb		
NEW!	CHADA4B500	HADA-4B500	635,090 Ft	1,549 €
		HADA-4B500 is a 4x500W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 5.6 Kg / 12.35 lb		
NEW!	CHADA4B750	HADA-4B750	778,590 Ft	1,899 €
		HADA-4B750 is a 4x750W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 6.0 Kg / 13.22 lb		
Ref.	Name	NXA SERIES	Lista ár HUF	RRP €
EOL	CNXA480	NXA 4-80	652,720 Ft	1,592 €
		4 in /4 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier (4 x 85W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 4 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88 x 373 mm. Weight 9.2 kg		
EOL	CNXA4200	NXA 4-200	908,970 Ft	2,217 €
		4 in /4 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier (4 x 202W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 4 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 12.6 kg		
EOL	CNXA4400	NXA 4-400	1,261,160 Ft	3,076 €
		4 in /4 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier (4 x 416W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 4 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 16.0 kg		
EOL	CNXA6200	NXA 6-200	1,091,010 Ft	2,661 €
		6 in /6 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier (6 x 218W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 6 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 14.1 kg		

COMMERCIAL AMPLIFIERS

Ref.	Name	AURA SERIES	Lista ár HUF	RRP €
NEW!	CAURA2H150	AURA-2H150	307,090 Ft	749 €
		Stereo amplifier with 2 x 150 WRMS @ 70/100V (high impedance) powered outputs. Its noiseless convection cooling, a very high efficiency and its adjustable auto stand-by function provide this amplifier with a true green profile. Dimensions 440 x 44(1RU) x 221mm. Weight 6.05 kg		
NEW!	CAURA4H150	AURA-4H150	450,590 Ft	1,099 €
		Multichannel amplifier with 4 x 150 WRMS @ 70/100V (high impedance) powered outputs. Its noiseless convection cooling, a very high efficiency and its auto stand-by function provide this amplifier with a true green profile. Dimensions 440 x 44(1RU) x 341mm. Weight 10.5 kg		
NEW!	CAURA2L150	AURA-2L150	225,090 Ft	549 €
		Stereo, 2x150 WRMS @ 4 Ω, high efficiency amplifier (class D). Auto stand-by function, fanless design 100% silent.. Dimensions 440 x 44(1RU) x 161 mm. Weight 2.60 kg		
NEW!	CAURA4L150	AURA-4L150	327,590 Ft	799 €
		4x150 WRMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function, fanless design 100% silent. Dimensions 482.6 x 44(1RU) x 221 mm. Weight 3.60 kg		
NEW!	CAURA8L150	AURA-8L150	614,590 Ft	1,499 €
		8x150 WRMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function, fanless design 100% silent. Dimensions 482.6 x 44(1RU) x 341 mm. Weight 6 kg		
Ref.	Name	eLPA SERIES	Lista ár HUF	RRP €
	CELPA2350	eLPA2-350	257,890 Ft	629 €
		Stereo amplifier delivering 2 x 345 WRMS @ 4Ω. Have 2 XLR balanced inputs, 2 Speakon® and terminal type connection outputs. Ultra light and versatile format. Built in crossover (150Hz), permanently activated anti-clip circuit and efficient progressive ventilation system. 2 Bridged Channels @ 8 Ω 560 WRMS. Dimensions 482.6 x 88(2RU) x 266 mm. Weight 5.50 kg		
	CELPA2650	eLPA2-650	330,870 Ft	807 €
		Stereo amplifier delivering 2 x 630 WRMS @ 4Ω. Have 2 XLR balanced inputs, 2 Speakon® and terminal type connection outputs. Ultra light and versatile format. Permanently activated anti-clip circuit and efficient progressive ventilation system. 2 Bridged Channels @ 8 Ω 1220 WRMS. Dimensions 482.6 x 88(2RU) x 266 mm / 6.00kg		
	CELPA2950	eLPA2-950	389,090 Ft	949 €
		Stereo amplifier delivering 2 x 950 WRMS @ 4Ω. Have 2 XLR balanced inputs, 2 Speakon® and terminal type connection outputs. Ultra light and versatile format. Permanently activated anti-clip circuit and efficient progressive ventilation system. 2 Bridged Channels @ 8 Ω 1840 WRMS. Dimensions 482,6 x 88(2RU)x 266 mm. Weight 6,15 kg		
	CELPA21400	eLPA2-1400	439,520 Ft	1,072 €
		Stereo amplifier delivering 2 x 1400 WRMS @ 4Ω. Have 2 XLR balanced inputs, 2 Speakon® and terminal type connection outputs. Ultra light and versatile format. Permanently activated anti-clip circuit and efficient progressive ventilation system. 2 Bridged Channels @ 8 Ω 2600 WRMS. Dimensions 482,6 x 88(2RU) x 304 mm. Weight 6,35 kg		


Ref.	Name	eGPA SERIES	Lista ár HUF	RRP €
CEGPA2150C	eGPA2-150	Stereo, 2x150 WRMS @ 4 Ω, high efficiency amplifier (class D). Auto stand-by function, fanless design 100% silent. 2 Bridged Channels @ 8Ω 280 WRMS. Dimensions 440 x 44(1RU) x 161 mm. Weight 2.60 kg	214,430 Ft	523 €
CEGPA2300	eGPA2-300	Stereo, 2x310 WRMS @ 4 Ω, high efficiency stereo amplifier (class D). Auto stand-by function, fanless design 100% silent. 2 Bridged Channels @ 8Ω 600 WRMS. Dimensions 440 x 44(1RU) x 221 mm. Weight 3.40 kg	286,590 Ft	699 €
CEGPA4150C	eGPA4-150	4x150 WRMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function, fanless design 100% silent. 2 Bridged Channels @ 8Ω 280 WRMS. Dimensions 482.6 x 44(1RU) x 221 mm. Weight 3.60 kg	322,670 Ft	787 €


Ref.	Name	GPA SERIES	Lista ár HUF	RRP €
CGPA2400ES	GPA2-400ES	Stereo amplifier delivering 2 x 350 WRMS @ 4 Ω. True green profile: high efficiency, auto stand-by function, 100% silent fanless design, Energy Star certified. 2 remote volume control ports and bridge mode 2 channels @ 8Ω 700 WRMS. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 10.8 kg	389,090 Ft	949 €
CGPA2800	GPA2-800	Stereo amplifier delivering 2 x 720 WRMS @ 4 Ω, and ready to drive 1000 WRMS @ 2Ω loudspeaker loads (4 x 8 Ω loudspeakers in parallel, per channel). True green profile: high efficiency, auto stand-by function, 100% silent fanless design. 2 remote volume control ports and bridge mode 2 Channels @ 8Ω 1150 WRMS. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 10.8 kg	532,590 Ft	1,299 €

Ref.	Name	eHSA SERIES	Lista ár HUF	RRP €
CEHSA2500	eHSA2-500	Multichannel amplifier with 2 x 500 WRMS @ 100V (high impedance) powered outputs. Includes 2 mono balanced inputs (Euroblock terminals) with stack outputs. Dispose of selectable HPF, thermal and overload protection, anti-clip system, and volume control trimmers on rear panel. Dimensions 482.6 x 88(2RU) x 365mm. Weight 6.3kg	384,990 Ft	939 €
CEHSA460	eHSA4-60	Multichannel amplifier Class D with 4x60 WRMS @ 70/100V (high impedance) powered outputs, and low impedance output. Its noiseless convection cooling, and its auto stand-by function provide this amplifier with a true green profile. Include link channel buttons, that allows to replicate the input channel signal in the adjacent one. Dimensions 482,6 x 44(1RU) x 280mm. Weight 7,8 kg	307,090 Ft	749 €
CEHSA4150C	eHSA4-150	Multichannel amplifier with 4 x 150 WRMS @ 70/100V (high impedance) powered outputs. Its noiseless convection cooling, a very high efficiency and its auto stand-by function provide this amplifier with a true green profile. Dimensions 440 x 44(1RU) x 341mm. Weight 10.5 kg	449,360 Ft	1,096 €
CEHSA4500	eHSA4-500	Multichannel amplifier with 4 x 500 WRMS @ 100V (high impedance) powered outputs. Includes 2 mono balanced inputs (Euroblock terminals) with stack outputs. Dispose of selectable HPF, thermal and overload protection, anti-clip system, and volume control trimmers on rear panel. Dimensions 482.6 x 88(2RU) x 365mm. Weight 7.6 kg	556,370 Ft	1,357 €
CHSA2400ES	HSA2-400ES	Stereo amplifier with low and high impedance powered outputs (2x400 WRMS). Includes 2 balanced inputs (XLR and Euroblock), 2 remote volume ports and Euroblock outputs. True green profile (Energy Star® Certification): auto stand-by function and noiseless convection cooling. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 16.4 kg	495,690 Ft	1,209 €


MIXING AMPLIFIERS


Ref.	Name	eHMA SERIES	Lista ár HUF	RRP €
CEHMA60C	eHMA60	Self-powered audio mixer including 1 MIC input and two MIC/LINE ST inputs. It features a 60W powered output that supports both low (4 Ω) and high impedance (70/100V) loudspeaker lines. It also includes an audio priority system, phantom power, 2 band tone control, auto stand-by mode, MUTE port and universal power supply unit (24 VDC IN). Dimensions 200x44x150 mm. Weight 1.9kg. 1UHRMKIT Rack Mount Kit included.	147,190 Ft	359 €
CEHMA120C	eHMA120	Stereo, Self-powered audio mixer including 3x MIC/LINE ST and 1x LINE ST input. It features a 95W powered mono output that supports both low (4Ω) and high impedance (70/100V) loudspeaker lines, with 2-ZONE ON/OFF switches. Includes audio priority system, pager (1 zone), phantom, 2 band tone control, auto stand-by, MUTE port and universal power supply unit (compatible with 24 VDC IN). Dimensions 435x44x120 mm. Weight 2.9kg 1UHRMKIT Rack Mount Kit included	217,710 Ft	531 €


CEHMA250 	eHMA250	Self-powered audio mixer including 2 MIC, 2 MIC/LINE ST and 2 LINE ST inputs. It features a 250W powered mono output that supports both low (4 and 8Ω) and high impedance (50/70/100V) loudspeaker lines, with 4-ZONE ON/OFF switches. Includes an audio priority system, Pager (1 zone), phantom power, remote control port (WpM), AUX/REC output, 2 band tone control, auto stand-by mode and MUTE port. Dimensions 435x220x44mm / 17,1"x8,7"x1,7"mm. Weight 3kg / 6.6lb.	341,530 Ft	833 €
--	-------------------------	---	-------------------	--------------


Ref.	Name	HMA SERIES	Lista ár HUF	RRP €
CHMA120 	HMA120	Self-powered mixer including an integrated media player (USB,SD) and 5 external audio inputs: 3 x LINE ST, 1 MIC/LINE and 1 MIC. It features a 120W powered output that supports both low (4Ω) and high impedance (70/100V) loudspeaker lines. It also includes a 2 level priority system, auto stand-by mode, 2 band control tone, AUX OUT and a remote control port WpM series compatible. Dimensions 210 x 88 x 230 mm. Weight 5.95 kg Compatible with the 2UHRMKIT Rack Mount Kit.	264,040 Ft	644 €


ULTRA COMPACT AMPLIFIERS

Ref.	Name	CA SERIES	Lista ár HUF	RRP €
CCA40 	CA40	2 x 20 WRMS @ 40 stereo compact amplifier with a balanced MIC input (includes phantom power, Talkover and noise gate) and 2 LINE inputs. 3 output modes (STEREO, PARALLEL and BRIDGE) and AUX output. 2 band control tone, IR remote control included, serial RS-232 port (EclerCOMM and CA-NET compatible) and 0-10 VDC remote port for WpM wall panel series (volume and source selection). Auto-standby function and MUTE port. Dimensions 155 x 155 x 45 mm. Weight 0.65 kg	140,220 Ft	342 €

CCA120C 	CA120	2 x 60 WRMS @ 40 stereo compact amplifier with a MIC/LINE input (includes phantom power, Talkover and noise gate) and 2 LINE inputs. AUX output. Control features: 2 band control tone, IR remote control included, serial RS-232 port (EclerCOMM and CA-NET compatible) and 0-10 VDC remote port for WpM wall panel series (volume and source selection). Auto-standby function and MUTE port. Dimensions 160 x 210 x 48 mm. Weight 0.95 kg	205,820 Ft	502 €
---	-----------------------	--	-------------------	--------------


CCA120HZC 	CA120HZ	High impedance version of the CA120, delivering 120W @ 70/100V line level, with a MIC/LINE input (includes phantom power, Talkover and noise gate) and 2 LINE inputs. AUX output. Control features: 2 band control tone, IR remote control included, serial RS-232 port (EclerCOMM and CA-NET compatible) and 0-10 VDC remote port for WpM wall panel series (volume and source selection). Auto-standby function and MUTE port. Dimensions 160 x 325 x 48 mm. Weight 2.92 kg	221,810 Ft	541 €
---	-------------------------	---	-------------------	--------------


Ref.	Name	eCA SERIES	Lista ár HUF	RRP €
CECA120C 	eCA120	2 x 60 WRMS @ 4 Ω stereo micro-amplifier, in a very compact format and a light and silent (fanless) design. It features 1 LINE ST input (RCA/Euroblock), AUTO STANDBY function and volume remote control, compatible with Ecler WpMVOL and WpMVOL-SR wall panels (0-10 VDC). Auto-standby function. External, universal and CE/UL/CCC certified power supply. Dimensions: 190 x 48 x 90mm. Weight 600 g.	166,870 Ft	407 €


CECA120HZC 	eCA120HZ	Mono micro-amplifier delivering 1 x 120 WRMS @ 70V / 100 V line level (high impedance), built in a very compact format and a light and silent (fanless) design. It features 1 LINE ST input (RCA/Euroblock), AUTO STANDBY function and volume remote control, compatible with WpMVOL and WpMVOL-SR wall panels (0-10 VDC). Auto-standby function. External, universal and CE/UL/CCC certified power supply. Dimensions: 190 x 48 x 190mm. Weight 2.3 kg	188,600 Ft	460 €
--	--------------------------	---	-------------------	--------------


LOUDSPEAKERS


IN-CEILING LOUDSPEAKERS


Ref.	Name		Lista ár HUF	RRP €
CIW10? 	IW103	3" in-ceiling / in-wall installation loudspeaker featuring a rectangular and discreet design, and including a high impedance transformer unit with 15 and 30 W power selections @ 100V line level. Dimensions 110 x 165 x 80 mm. Weight 900g. Delivered by master carton of 8 units. Price per unit.	31,570 Ft	77 €


Ref.	Name	eIC SERIES	Lista ár HUF	RRP €
CEIC51FM 	eIC51FM	Fast installation in-ceiling loudspeaker. It features a 4,5" woofer, 6 WRMS @ 8 Ω nominal power and 70/100V line transformer with 3 and 6 W power selections. Internal diameter 150 mm. External diameter 160mm. Required depth 54mm. Weight 500g. Price per unit.	9,020 Ft	22 €


CEIC52		eIC52	2-way cost-effective in-ceiling loudspeaker with a great sound performance. It features a 5,25" woofer and a 0,75" tweeter, 20 WRMS @ 8 Ω nominal power and 100V line transformer with 3 and 6 W power selections. Internal diameter 164mm. External diameter 202mm. Required depth: 65mm. Weight 1.0 kg Delivered by master carton of 8 units. Price per unit.	16,810 Ft	41 €
---------------	---	-----------------------	--	------------------	-------------


CEIC52MS		eIC52MS	2-way in-ceiling loudspeaker suitable for installations exposed to extreme humidity and/or temperature. It features 1x5" woofer and 1x1" tweeter with a global power admission of 20 WRMS @ 8Ω. Internal diameter 120mm. External diameter 165mm. Required depth 79mm. Weight 700g. Delivered by units. Price per unit.	25,010 Ft	61 €
-----------------	---	-------------------------	---	------------------	-------------


Ref.	Name	IC SERIES		Lista ár HUF	RRP €
CIC3BK		IC3	1-way loudspeaker is the perfect option for 70/100 V (0.75/1.5/3/6 W) and low impedance sound solutions. It mounts a 3" woofer in a discreet design. Cutout size 90mm. Internal diameter 88mm. External diameter 105mm. Required depth 90mm. Weight 500g. Black colour. Delivered by master carton of 2 units. Price per unit.	19,680 Ft	48 €


CIC3WH		IC3	1-way loudspeaker is the perfect option for 70/100 V (0.75/1.5/3/6 W) and low impedance sound solutions. It mounts a 3" woofer in a discreet design. Cutout size 90mm. Internal diameter 88mm. External diameter 105mm. Required depth 90mm. White colour. Weight 500g. Delivered by master carton of 2 units. Price per unit.	19,680 Ft	48 €
---------------	---	---------------------	--	------------------	-------------


CIC6BK		IC6BK	2-way loudspeaker is the perfect option for 70/100 V (2.5/5/7.5/15 W) and low impedance sound solutions (40 WRMS @8Ω). It mounts a 6" woofer and a 1" tweeter in a discreet design. Cutout size 180mm. Internal diameter 178mm. External diameter 204mm. Required depth 73mm. Weight 1,52kg Delivered by master carton of 2 units. Price per unit. Black colour.	27,880 Ft	68 €
---------------	---	-----------------------	---	------------------	-------------




CIC6		IC6	2-way loudspeaker is the perfect option for 70/100 V (2.5/5/7.5/15 W) and low impedance sound solutions (40 WRMS @8Ω). It mounts a 6" woofer and a 1" tweeter in a discreet design. Cutout size 180mm. Internal diameter 178mm. External diameter 204mm. Required depth 73mm. Weight 1,52kg Delivered by master carton of 2 units. Price per unit. White colour.	27,880 Ft	68 €
-------------	---	---------------------	---	------------------	-------------

CIC8		IC8	2-way loudspeaker is the perfect option for 70/100 V (5/7.5/15/30 W) and low impedance sound solutions (60 WRMS @8Ω). It mounts an 8" woofer and a 1" tweeter in a discreet design. Cutout size 222mm. Internal diameter 220mm. External diameter 245mm. Required depth 91mm. Weight 2,3kg Delivered by master carton of 2 units. Price per unit. White colour.	37,720 Ft	92 €
-------------	---	---------------------	--	------------------	-------------







Ref.	Name	VIC SERIES		Lista ár HUF	RRP €
CVIC6		VIC6	2-way loudspeaker is the perfect option for 70/100 V (2,5/5/10/20/40 W) and low impedance sound solutions (40 WRMS @8Ω). It mounts a 6,5" woofer and a 0,5" steerable tweeter in a discreet design. Dimensions (ØxD): 232x105mm. Weight 1,8kg. Delivered by master carton of 2 units. Price per unit.	43,050 Ft	105 €



CVIC6X		VIC6X	2-way loudspeaker is the perfect option for 70/100 V (2,5/5/10/20/40 W) and low impedance sound solutions (40 WRMS @8Ω). It mounts a 6,5" woofer and a 0,5" steerable tweeter in a discreet design. With plastic back can and tile bridge. Dimensions (ØxD): 232x170mm. Weight 1,8kg. Delivered by master carton of 2 units. Price per unit.	68,470 Ft	167 €
---------------	---	-----------------------	---	------------------	--------------

CVIC8		VIC8	2-way loudspeaker is the perfect option for 70/100 V (3,75/7,5/15/30/60 W) and low impedance sound solutions (60 WRMS @8Ω). It mounts an 8" woofer and a 0,5" steerable tweeter in a discreet design. Dimensions (ØxD): 282x115mm. Weight 2,3kg. Delivered by master carton of 2 units. Price per unit.	54,530 Ft	133 €
--------------	---	----------------------	--	------------------	--------------

	CVIC8X VIC8X	2-way loudspeaker is the perfect option for 70/100 V (3,75/7,5/15/30/60 W) and low impedance sound solutions (60 WRMS @8Ω). It mounts an 8" woofer and a 0,5" steerable tweeter in a discreet design. With plastic back can and tile bridge. Dimensions (ØxD): 282x200mm. Weight 3,1kg. Delivered by master carton of 2 units. Price per unit.	97,170 Ft	237 €
	CVICSB81 VICSB8	Sub-woofer reinforcement loudspeaker is the perfect option for 70/100 V (3,75/7,5/15/30/60 W) and low impedance sound solutions. It mounts an 8" providing 80 WRMS power in a discreet design. Dimensions (ØxD): 282x135mm. Weight 3,1kg. Delivered by units. Price per unit.	97,170 Ft	237 €
	CVICSB8X VICSB8X	Sub-woofer reinforcement loudspeaker is the perfect option for 70/100 V (3,75/7,5/15/30/60 W) and low impedance sound solutions. It mounts an 8" providing 80 WRMS power in a discreet design. With plastic back can and tile bridge. Dimensions (ØxD): 282x200mm. Weight 3,9kg. Delivered by master carton of 2 units. Price per unit.	140,220 Ft	342 €

HIGH PERFORMANCE LOUDSPEAKERS

Ref.	Name	MIA SERIES	Lista ár HUF	RRP €	
NEW!	CMIA81BK 	MIA-81	MIA-81 is an elegant, unique a compact design column loudspeaker, built in a single aluminium piece to avoid vibrations and mechanical stress. MIA-81 includes 8x1.5" drivers delivering 40WRMS and the possibility of working in 16 Ω or 64 Ω. IP44 rated. Includes FLATY bracket made out of stainless-steel that permits adjusting the height at any point of the length of the column. Black colour. Dimensions 58 x 448 x 67 mm / 2.28 x 17.64 x 2.64 in. (WxHxD). Weight 1.2 kg / 1.64 lb. Delivered by units. Price per unit.	237,390 Ft	579 €
NEW!	CMIA81WH 	MIA-81	MIA-81 is an elegant, unique a compact design column loudspeaker, built in a single aluminium piece to avoid vibrations and mechanical stress. MIA-81 includes 8x1.5" drivers delivering 40WRMS and the possibility of working in 16 Ω or 64 Ω. IP44 rated. Includes FLATY bracket made out of stainless-steel that permits adjusting the height at any point of the length of the column. White colour. Dimensions 58 x 448 x 67 mm / 2.28 x 17.64 x 2.64 in. (WxHxD). Weight 1.2 kg / 1.64 lb. Delivered by units. Price per unit.	237,390 Ft	579 €
NEW!	CMIA82BK 	MIA-82	MIA-82 is an elegant, unique a compact design column loudspeaker, built in a single aluminium piece to avoid vibrations and mechanical stress. MIA-82 includes 8x2.5" drivers delivering 150WRMS and the possibility of working in 16 Ω or 64 Ω. IP44 rated. Includes the versatile smart pan and tilt bracket HANDY made out of stainless-steel that permits adjusting the height at any point of the length of the column. Black colour. Dimensions 83 x 648 x 87 mm / 3.27 x 25.51 x 3.43 in. (WxHxD). Weight 2.65 kg / 5.84 lb. Delivered by units. Price per unit.	298,890 Ft	729 €
NEW!	CMIA82WH 	MIA-82	MIA-82 is an elegant, unique a compact design column loudspeaker, built in a single aluminium piece to avoid vibrations and mechanical stress. MIA-82 includes 8x2.5" drivers delivering 150WRMS and the possibility of working in 16 Ω or 64 Ω. IP44 rated. Includes the versatile smart pan and tilt bracket HANDY made out of stainless-steel that permits adjusting the height at any point of the length of the column. White colour. Dimensions 83 x 648 x 87 mm / 3.27 x 25.51 x 3.43 in. (WxHxD). Weight 2.65 kg / 5.84 lb. Delivered by units. Price per unit.	298,890 Ft	729 €
Ref.	Name	NIMBO SERIES	Lista ár HUF	RRP €	
NEW!	CNIMBO14WH 	NIMBO-14	2-way passive loudspeaker for surface mounting (1x 4" woofers and 1" tweeter). 40 WRMS @ 8 ohm. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. White color. Dimensions 250 x 148.7x 150 mm / 9.84 x 5.85 x 5.91 in. Weight 1.7 kg / 3.75 lb. Delivered by units. Price per unit.	137,350 Ft	335 €
NEW!	CNIMBO14BK 	NIMBO-14	2-way passive loudspeaker for surface mounting (1x 4" woofers and 1" tweeter). 40 WRMS @ 8 ohm. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Black color. Dimensions 250 x 148.7x 150 mm / 9.84 x 5.85 x 5.91 in. Weight 1.7 kg / 3.75 lb. Delivered by units. Price per unit.	137,350 Ft	335 €

NEW!	CNIMBO14GD 	NIMBO-14	2-way passive loudspeaker for surface mounting (1x 4" woofers and 1" tweeter). 40 WRMS @ 8 ohm. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Gold color. Dimensions 250 x 148.7x 150 mm / 9.84 x 5.85 x 5.91 in. Weight 1.7 kg / 3.75 lb. Delivered by units. Price per unit.	137,350 Ft	335 €
NEW!	CNIMBO14TN  Available in 2025	NIMBO-14	2-way passive loudspeaker for surface mounting (1x 4" woofers and 1" tweeter). 40 WRMS @ 8 ohm. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Titanium color. Dimensions 250 x 148.7x 150 mm / 9.84 x 5.85 x 5.91 in. Weight 1.7 kg / 3.75 lb. Delivered by units. Price per unit.	137,350 Ft	335 €
NEW!	CNIMBO14CR 	NIMBO-14	NIMBO-14 cabinet RAL customization (black grill and bracket). MOQ: 8 units. Delivery time: 45 days. Dimensions 250 x 148.7x 150 mm / 9.84 x 5.85 x 5.91 in. Weight 1.7 kg / 3.75 lb. Delivered by units. Price per unit.	157,850 Ft	385 €
NEW!	CNIMBO24WH 	NIMBO-24	2-way passive loudspeaker for surface mounting (2x 4" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 80 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. White color. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.	200,900 Ft	490 €
NEW!	CNIMBO24BK 	NIMBO-24	2-way passive loudspeaker for surface mounting (2x 4" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 80 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Black color. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.	200,900 Ft	490 €
NEW!	CNIMBO24GD 	NIMBO-24	2-way passive loudspeaker for surface mounting (2x 4" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 80 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Gold color. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.	200,900 Ft	490 €
NEW!	CNIMBO24TN  Available in 2025	NIMBO-24	2-way passive loudspeaker for surface mounting (2x 4" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 80 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Titanium color. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.	200,900 Ft	490 €
NEW!	CNIMBO24CR 	NIMBO-24	NIMBO-24 cabinet RAL customization (black grill and bracket). MOQ: 8 units. Delivery time: 45 days. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.	231,240 Ft	564 €
NEW!	CNIMBO26WH 	NIMBO-26	2-way passive loudspeaker for surface mounting (2x 6" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 140 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. White color. Dimensions 542,5 x 261 x 269 mm. / 21.35"x 10.27"x 10.59". Weight 8,5 kg. / 18.73 lb. Delivered by units. Price per unit.	364,900 Ft	890 €

NEW!	CNIMBO26BK	NIMBO-26	2-way passive loudspeaker for surface mounting (2x 6" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 140 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Black color. Dimensions 542,5 x 261 x 269 mm. / 21.35"x 10.27"x 10.59". Weight 8,5 kg. / 18.73 lb. Delivered by units. Price per unit.	364,900 Ft	890 €
-------------	-------------------	--------------------------	--	-------------------	--------------



NEW!	CNIMBO26GD	NIMBO-26	2-way passive loudspeaker for surface mounting (2x 6" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 140 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Gold color. Dimensions 542,5 x 261 x 269 mm. / 21.35"x 10.27"x 10.59". Weight 8,5 kg. / 18.73 lb. Delivered by units. Price per unit.	364,900 Ft	890 €
-------------	-------------------	--------------------------	---	-------------------	--------------



NEW!	CNIMBO26TN	NIMBO-26	2-way passive loudspeaker for surface mounting (2x 6" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 140 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Titanium color. Dimensions 542,5 x 261 x 269 mm. / 21.35"x 10.27"x 10.59". Weight 8,5 kg. / 18.73 lb. Delivered by units. Price per unit.	364,900 Ft	890 €
-------------	-------------------	--------------------------	---	-------------------	--------------



Available in 2025

NEW!	CNIMBO26CR	NIMBO-26	NIMBO-26 cabinet RAL customization (black grill and bracket). MOQ: 8 units. Delivery time: 45 days. Dimensions 542,5 x 261 x 269 mm. / 21.35"x 10.27"x 10.59". Weight 8,5 kg. / 18.73 lb. Delivered by units. Price per unit.	419,430 Ft	1,023 €
-------------	-------------------	--------------------------	---	-------------------	----------------



Ref.	Name	NIMBO Merchandising	Lista ár HUF	RRP €	
NEW!	CMNIMBOSCREW	NIMBOSCREW	Set of 24 small precision screwdrivers, with silk-screened NIMBO logo. Presented in an ABS magnetic box with snap-opening. Dimensions: 60 x 160 x 15 mm / 2.32" x 6.29" x 0.59". Weight: 220gr / 0,48 lb. Price per unit.	9,840 Ft	24 €



Ref.	Name	ARQIS SERIES	Lista ár HUF	RRP €	
	CARQIS105IB	ARQIS 105IBK	2-way (5,25" woofer and 1" HF tweeter) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 70 WRMS @ 8 Ω. 280W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. Double INPUT/STACK connector, Euroblock type, with security attachment screws, and metal safety sling included. 150°x130° dispersion pattern. Dimensions (WxHxD) 186 x 280 x 210 mm / 7,32 x 11,02 x 8,26 in. Weight 3.6 kg. Black color	101,680 Ft	248 €



	CARQIS105IW	ARQIS 105IWH	2-way (5,25" woofer and 1" HF tweeter) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 70 WRMS @ 8 Ω. 280W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. Double INPUT/STACK connector, Euroblock type, with security attachment screws, and metal safety sling included. 150°x130° dispersion pattern. Dimensions (WxHxD) 186 x 280 x 210 mm / 7,32 x 11,02 x 8,26 in. Weight 3.6 kg. White color	101,680 Ft	248 €
--	--------------------	------------------------------	--	-------------------	--------------



	CARQIS106IB	ARQIS 106IBK	2-way (6" woofer and 1" rotatable HF Compressor Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 120 WRMS@8Ω. 480W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. Double INPUT/STACK connector, Euroblock type, with security attachment screws, and metal safety sling included. 140°x160° dispersion pattern. Dimensions (WxHxD) 216x350x240mm / 8.50"x13.78"x9.45". Weight 7,4 kg / 16.31 lb. Black color	138,580 Ft	338 €
--	--------------------	------------------------------	---	-------------------	--------------



CARQIS106IW	ARQIS 106IWH	2-way (6" woofer and 1" rotatable HF Compressor Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 120 WRMS@8Ω.480W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. Double INPUT/STACK connector, Euroblock type, with security attachment screws, and metal safety sling included. 140°x160° dispersion pattern. Dimensions (WxHxD) 216x350x240mm / 8.50"x13.78"x9.45". Weight 7,4 kg / 16.31 lb. White color	138,580 Ft	338 €
CARQIS108IB	ARQIS 108IBK	2-way (8" woofer and 1" HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics, excellent sound quality and long term reliability, featuring 150 WRMS @ 8 Ω. 600W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. 130°x130° dispersion pattern. Dimensions (WxHxD) 244 x 390 x 280 mm / 9.60" x 15.35" x 11.02". Weight 8,4 kg / 18.52 lb. Black color.	164,000 Ft	400 €
CARQIS108IW	ARQIS 108IWH	2-way (8" woofer and 1" HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics, excellent sound quality and long term reliability, featuring 150 WRMS @ 8 Ω. 600W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. 130°x130° dispersion pattern. Dimensions (WxHxD) 244 x 390 x 280 mm / 9.60" x 15.35" x 11.02". Weight 8,4 kg / 18.52 lb. White color	164,000 Ft	400 €
CARQIS110IB	ARQIS 110IBK	2-way (10" woofer and 1" rotatable HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics and long term reliability, featuring 300 WRMS @ 8 ohm. 1200W Peak power. 35 mm mount socket and 8 x M10 rigging points, allowing for horizontal or vertical mounting options (110°x 110° dispersion pattern). Dimensions (WxHxD) 359x495x310mm / 14.13"x19.49"x13.86". Weight 14,8 kg / 32.63 lb Black color. Bracket not included. Optional ARQ110UB, TRIPO and SR12 accessories.	217,300 Ft	530 €
CARQIS110IW	ARQIS 110IWH	2-way (10" woofer and 1" rotatable HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics and long term reliability, featuring 300 WRMS @ 8 ohm. 1200W Peak power. 35 mm mount socket and 8 x M10 rigging points, allowing for horizontal or vertical mounting options (110°x 110° dispersion pattern). Dimensions (WxHxD) 359x495x310mm / 14.13"x19.49"x13.86". Weight 14,8 kg / 32.63 lb White color. Bracket not included. Optional ARQ110UB, TRIPO and SR12 accessories.	217,300 Ft	530 €
CARQIS112IB	ARQIS 112IBK	2-way (12" woofer and 1,4" rotatable HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics and long term reliability, featuring 500 WRMS @ 8 Ω. 2000W Peak power. 35 mm mount socket and 8 x M10 rigging points, allowing for horizontal or vertical mounting options (120°x 110° dispersion pattern). Dimensions (WxHxD)416x565x352mm / 16.37"x22.24"x13.86". Weight 20,0 kg / 44.09 lb. Black color. Bracket not included. Optional ARQ112UB, TRIPO and SR12 accessories.	320,620 Ft	782 €
CARQIS112IW	ARQIS 112IWH	2-way (12" woofer and 1,4" rotatable HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics and long term reliability, featuring 500 WRMS @ 8 Ω. 2000W Peak power. 35 mm mount socket and 8 x M10 rigging points, allowing for horizontal or vertical mounting options (120°x 110° dispersion pattern). Dimensions (WxHxD)416x565x352mm / 16.37"x22.24"x13.86". Weight 20,0 kg / 44.09 lb. White color. Bracket not included. Optional ARQ112UB, TRIPO and SR12 accessories.	320,620 Ft	782 €
CARQIS205IB	ARQIS 205IBK	2-way (2x 5,25" woofer and 1" HF rotatable Compression Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 140 WRMS @ 8 Ω. 560W Peak power. Double INPUT/STACK connector, Euroblock + Speakon® type, 8 x M8 cabinet flying points, metal safety sling included. Its "U" shape wall bracket (included) allows for tilt adjustment. 150° x 40° dispersion pattern. Dimensions (WxHxD) 480x186x210mm / 18.89"x7.32"x8.26". Weight 8.4 kg. / 18.52 lb Black color.	161,540 Ft	394 €

CARQIS205IW	ARQIS 205IWH	2-way (2x 5,25" woofer and 1" HF rotatable Compression Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 140 WRMS @ 8 Ω. 560W Peak power. Double INPUT/STACK connector, Euroblock + Speakon® type, 8 x M8 cabinet flying points, metal safety sling included. Its "U" shape wall bracket (included) allows for tilt adjustment. 150° x 40° dispersion pattern. Dimensions (WxHxD) 480x186x210mm / 18.89"x7.32"x8.26". Weight 8.4 kg / 18.52 lb. White color.	161,540 Ft	394 €
--------------------	------------------------------	--	-------------------	--------------



CARQIS208IB	ARQIS 208IBK	2-way (2 x 8" woofer and 1" HF Compression Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 300 WRMS @ 8 Ω. 1200W Peak power. Double INPUT/STACK connector, Euroblock + Speakon® type, 8 x M8 cabinet flying points, metal safety sling included. Its "U" shape wall bracket (included) allows for tilt adjustment. 130°x30° dispersion pattern. Dimensions(WxHxD) 610x244x280mm / 24.01"x9.60"x11.02". Weight 14.4 kg / 31.74 lb. Black color.	248,870 Ft	607 €
--------------------	------------------------------	--	-------------------	--------------



CARQIS208IW	ARQIS 208IWH	2-way (2 x 8" woofer and 1" HF Compression Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 300 WRMS @ 8 Ω. 1200W Peak power. Double INPUT/STACK connector, Euroblock + Speakon® type, 8 x M8 cabinet flying points, metal safety sling included. Its "U" shape wall bracket (included) allows for tilt adjustment. 130°x30° dispersion pattern. Dimensions(WxHxD) 610x244x280mm / 24.01"x9.60"x11.02". Weight 14.4 kg / 31.74 lb. White color.	248,870 Ft	607 €
--------------------	------------------------------	--	-------------------	--------------



Ref.	Name		Lista ár HUF	RRP €
------	------	--	--------------	-------

CLAB1C100I	LAB1-C100i	LAB1-C100i is a versatile and discreet column loudspeaker, designed for indoor and outdoor fixed installations and portable applications. It features twelve 3" drivers with 0.75" neodymium voice coil each one, 300W AES. Its versatile profile allows the column to be installed in several ways such on the LAB1 subwoofers, on wall, pole, truss, etc. thanks to LAB1 accessories. Stand alone or combined with other LAB1-C100i and LAB1-SP18p to create a complete powerful plug & play solution. Dimensions: 89 x 1000 x 117 mm / 3.5" x 39.4" x 4.6". Weight: 7.8 kg / 17.2 lb.	548,170 Ft	1,337 €
-------------------	----------------------------	--	-------------------	----------------



Ref.	Name		Lista ár HUF	RRP €
------	------	--	--------------	-------

CDROP6BK	DROP6	ECLER DROP6 is a 2-way 6.5", 75W@8ohm pendant loudspeaker with a stylish design, including a 70/100V line transformer with 60/30/15 and 7,5W power selections, available at both high and low impedance levels. Dimensions (without accessories) Ø270mm x 355mm(H) / Ø10.6 in. x 14 in. (H). Weight 4.2 Kg / 9.26 lb. Stripped wire connection (5m). Black colour.	125,050 Ft	305 €
-----------------	-----------------------	--	-------------------	--------------



CDROP6WH	DROP6	ECLER DROP6 is a 2-way 6.5", 75W@8ohm pendant loudspeaker with a stylish design, including a 70/100V line transformer with 60/30/15 and 7,5W power selections, available at both high and low impedance levels. Dimensions (without accessories) Ø270mm x 355mm(H) / Ø10.6 in. x 14 in. (H). Weight 4.2 Kg / 9.26 lb. 2x stripped wire connection (5m). White colour.	125,050 Ft	305 €
-----------------	-----------------------	---	-------------------	--------------




Ref.	Name		Lista ár HUF	RRP €
------	------	--	--------------	-------

NEW! CZEN15GR	ZEN-15	The new ZEN-15 in-ground loudspeaker with an elegant rounded rock shape seamlessly blends the world of audio technology with the aesthetics of nature. Includes a 5,25" woofer and a 1" tweeter delivering 70W RMS @ 8ohm and 60W RMS @ 70/100V. This discreet outdoor audio solution effortlessly integrates into outdoor environments, providing a harmonious balance between functionality and visual appeal. Grey color. Dimensions 410 x 260 x 289mm / 16.14 x 10.23 x 11,37 in. Weight 4.4Kg / 9.7lb	155,390 Ft	379 €
-----------------------------	------------------------	--	-------------------	--------------





NEW! CZEN15SD	ZEN-15	The new ZEN-15 in-ground loudspeaker with an elegant rounded rock shape seamlessly blends the world of audio technology with the aesthetics of nature. Includes a 5,25" woofer and a 1" tweeter delivering 70W RMS @ 8ohm and 60W RMS @ 70/100V. Crafted to resemble a rugged, weathered stone, this discreet outdoor audio solution effortlessly integrates into outdoor environments, providing a harmonious balance between functionality and visual appeal. Sand color. Dimensions 410 x 260 x 289mm / 16.14 x 10.23 x 11,37 in. Weight 4.4Kg / 9.7lb	155,390 Ft	379 €
-----------------------------	------------------------	---	-------------------	--------------





Ref.	Name		Lista ár HUF	RRP €	
CIG108	IG108		Weatherproof loudspeaker (IP65) with an omni-directional horizontal dispersion pattern (360°). 8" Kevlar woofer and 1" ACCW silk tweeter. 100 WRMS @ 8Ω, suitable for 70/100V (7.5/15/30/60 W @ 100V). Frequency response 50Hz to 23kHz.Security ground bracket included. It is ideal for music and message applications in outdoor areas. Dimensions 360 x 392.5 mm. Weight 8.5 kg	186,140 Ft	454 €


COMMERCIAL LOUDSPEAKERS


Ref.	Name		Lista ár HUF	RRP €	
CTRAIL103BK	TRAIL103BK		3" lamp style loudspeaker cabinet, with high Impedance (15W and 30W taps) and Low Impedance (15 WRMS @4Ω) connections. Includes 3 different installation system accessories for ceiling light rails, surface mount and truss mount. Dimensions (without arm) Ø 96mm x 110mm. Weight 1kg Black colour. Delivered by units. Price per unit.	91,430 Ft	223 €


CTRAIL103WH	TRAIL103WH		3" lamp style loudspeaker cabinet, with high Impedance (15W and 30W taps) and Low Impedance (15 WRMS @4Ω) connections. Includes 3 different installation system accessories for ceiling light rails, surface mount and truss mount. Dimensions (without arm) Ø 96mm x 110mm. Weight 1kg White colour. Delivered by units. Price per unit.	91,430 Ft	223 €
--------------------	----------------------------	---	---	------------------	--------------


Ref.	Name	eAMBIT SERIES	Lista ár HUF	RRP €		
EOL	CEAMB103BK	eAMBIT103BK		Ultra compact 2-way (3.5" woofer and 0.5" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (2.5/5/7.5/15 W) and low impedance (25 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation.Dimensions (without accessories) 120 x 120 x 117 mm. Weight 1,275kg Black color. Delivered by master carton of 2 units. Price per unit.	28,700 Ft	70 €


EOL	CEAMB103WH	eAMBIT103WH		Ultra compact 2-way (3.5" woofer and 0.5" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (2.5/5/7.5/15 W) and low impedance (25 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation.Dimensions (without accessories) 120 x 120 x 117 mm. Weight 1,275kg White color. Delivered by master carton of 2 units. Price per unit.	28,700 Ft	70 €
------------	-------------------	-----------------------------	--	---	------------------	-------------


EOL	CEAMB106WH	eAMBIT106WH		Ultra compact 2-way (6.5" woofer and 1" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (5/7.5/15/30 W) and low impedance(50 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation. Dimensions (without accessories) 210 x 210 x 160 mm. Weight 2,75kg White color. Delivered by master carton of 2 units. Price per unit.	47,560 Ft	116 €
------------	-------------------	-----------------------------	---	---	------------------	--------------


Ref.	Name	AMBIT SERIES	Lista ár HUF	RRP €		
NEW!	CAMBIT13BK	AMBIT-13		Ultra compact 2-way (3.5" woofer and 0.5" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (2.5/5/7.5/15 W) and low impedance (25 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation.Dimensions (without accessories) 120 x 120 x 117 mm. Weight 1,275kg Black color. Delivered by master carton of 2 units. Price per unit.	28,700 Ft	70 €


NEW!	CAMBIT13WH	AMBIT-13		Ultra compact 2-way (3.5" woofer and 0.5" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (2.5/5/7.5/15 W) and low impedance (25 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation.Dimensions (without accessories) 120 x 120 x 117 mm. Weight 1,275kg White color. Delivered by master carton of 2 units. Price per unit.	28,700 Ft	70 €
-------------	-------------------	-----------------	---	---	------------------	-------------


NEW!	CAMBIT16BK	AMBIT-16		Ultra compact 2-way (6.5" woofer and 1" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (5/7.5/15/30 W) and low impedance(50 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation.Dimensions (without accessories) 210 x 210 x 160 mm. Weight 2,75kg Black color. Delivered by master carton of 2 units. Price per unit.	47,560 Ft	116 €
-------------	-------------------	-----------------	---	--	------------------	--------------


NEW!	CAMBIT16WH 	AMBIT-16	Ultra compact 2-way (6.5" woofer and 1" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (5/7.5/15/30 W) and low impedance(50 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation. Dimensions (without accessories) 210 x 210 x 160 mm. Weight 2,75kg White color. Delivered by master carton of 2 units. Price per unit.	47,560 Ft	116 €
-------------	--	-----------------	---	------------------	--------------


NEW!	CAMBIT18BK 	AMBIT-18	Ultra compact 2-way (8" woofer and 1,18" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (60 W) and low impedance(75 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation. Dimensions (without accessories) 258 x 258 x 225 mm. Weight 5.6k.g Black color. Delivered by master carton of 2 units. Price per unit.	97,990 Ft	239 €
-------------	--	-----------------	---	------------------	--------------


NEW!	CAMBIT18WH 	AMBIT-18	Ultra compact 2-way (8" woofer and 1,18" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (60 W) and low impedance(100 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation. Dimensions (without accessories) 258 x 258 x 225 mm. Weight 5.6k.g. White color. Delivered by master carton of 2 units. Price per unit.	97,990 Ft	239 €
-------------	--	-----------------	---	------------------	--------------


Ref.	Name	AUDEO SERIES	Lista ár HUF	RRP €	
EOL	CAUDEO103BK 	AUDEO103BK	2-way loudspeaker cabinet. It features a 3.5" woofer and 0.5" tweeter. Suitable for high 70/100V (2.5/5/7.5/15 W) and low impedance (25 WRMS @8Ω) audio lines. Program power 50W. IP54 rated, protective front grill with anti-rust treatment, and accessories for wall-mounting included. Dimensions (without accessories) 132 x 134 x 110 mm. Weight 1,45kg Black color. Delivered by master carton of 2 units. Price per unit.	50,020 Ft	122 €


EOL	CAUDEO106BK 	AUDEO106BK	2-way loudspeaker cabinet. It features a 6.5" woofer and 1" tweeter. Suitable for 70/100V (5/7.5/15/30 W) and low impedance (50 WRMS @8Ω) audio lines. Program power 100W. IP54 rated, protective front grill with anti-rust treatment, and accessories for wall-mounting included. Dimensions (without accessories) 242 x 242 x 163 mm. Weight 2,3kg Black color. Delivered by master carton of 2 units. Price per unit.	74,620 Ft	182 €
------------	---	----------------------------	---	------------------	--------------










EOL	CAUDEO106WH 	AUDEO106WH	2-way loudspeaker cabinet. It features a 6.5" woofer and 1" tweeter. Suitable for 70/100V (5/7.5/15/30 W) and low impedance (50 WRMS @8Ω) audio lines. Program power 100W. IP54 rated, protective front grill with anti-rust treatment, and accessories for wall-mounting included. Dimensions (without accessories) 242 x 242 x 163 mmWeight 2,3kg White color. Delivered by master carton of 2 units. Price per unit.	74,620 Ft	182 €
------------	---	----------------------------	---	------------------	--------------

Ref.	Name	eMOTUS SERIES	Lista ár HUF	RRP €	
NEW!	CEMOTUS30DWH 	eMOTUS30DWH	3" woofer (25 WRMS @ 8Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for 70/100V and low impedance(8Ω) audio lines. Includes wall bracket and security steel cable. Dimensions (without accessories) 132x132x117 mm. Weight 1.3 kg White colour. Price per unit, sold in pairs.	36,490 Ft	89 €

NEW!	CEMOTUS30DBK 	eMOTUS30DBK	3" woofer (25 WRMS @ 8Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for 70/100V and low impedance(8Ω) audio lines. Includes wall bracket and security steel cable. Dimensions (without accessories) 132x132x117 mm. Weight 1.3 kg Black colour. Price per unit, sold in pairs.	36,490 Ft	89 €
-------------	--	-----------------------------	--	------------------	-------------

	CEMOTUS5PBWC 	eMOTUS5PBWH	Stereo loudspeaker kit (2 x 25 WRMS @ 8Ω) including an active and a passive cabinet. eMOTUS5PBBK performs BT connection, balanced and unbalanced audio inputs. Includes an IR remote control and 0-10VDC remote port. Features: source selection, 2 band tone control, stereo/mono switch, auto stand-by and wall bracket and security steel cable. Dimensions 173x185x180mm. Weight 2.1 kg. White colour. Delivered by kit (active + passive loudspeakers). Price per kit.	138,580 Ft	338 €
--	--	-----------------------------	---	-------------------	--------------

	CEMOTUS5PWHC 	eMOTUS5PWH	Stereo loudspeaker kit (2 x 25 WRMS @ 8Ω) including an active and a passive cabinet and performing 2 audio inputs: balanced and unbalanced. Suitable for low impedance audio lines, includes source selection, 2 band tone control, stereo/mono switch, auto stand-by and wall bracket and security steel cable. Dimensions (without accessories) 173x185x180mm. Weight 2.1 kg White colour. Delivered by kit (active + passive loudspeakers). Price per kit.	106,190 Ft	259 €
--	--	----------------------------	---	-------------------	--------------

NEW!	CEMOTUSSPBKC 	eMOTUSSPBK	Stereo loudspeaker kit (2 x 25 WRMS @ 8Ω) including an active and a passive cabinet and performing 2 audio inputs: balanced and unbalanced. Suitable for low impedance audio lines, includes source selection, 2 band tone control, stereo/mono switch, auto stand-by and wall bracket and security steel cable. Dimensions (without accessories) 173x185x180mm. Weight 2.1 kg Black colour. Delivered by kit (active + passive loudspeakers). Price per kit.	106,190 Ft	259 €
	CEMOTUSSODBK 	eMOTUSSODBK	5" woofer and 1" tweeter (40 WRMS @ 8Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for 100V (3,75/7,5/15/30W) and low impedance(8Ω) audio lines. Includes wall bracket and security steel cable. Dimensions (without accessories) 173x181x180mm. Weight 2.4 kg Black colour. Price per unit, sold in pairs.	58,630 Ft	143 €
	CEMOTUSSODWH 	eMOTUSSODWH	5" woofer and 1" tweeter (40 WRMS @ 8Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for 100V (3,75/7,5/15/30W) and low impedance(8Ω) audio lines. Includes a wall bracket and security steel cable. Dimensions (without accessories) 173x181x180mm. Weight 2.4 kg White colour. Price per unit, sold in pairs.	58,630 Ft	143 €
NEW!	CEMOTUSSO16B  Available in 2025	eMOTUSSO16	5" woofer and 1" tweeter (40 WRMS @ 16Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for low impedance(16Ω) audio lines. Includes a wall bracket and security steel cable. Dimensions (without accessories) 173x181x180mm. Weight 2.4 kg. Black colour. Price per unit, sold in pairs.	52,890 Ft	129 €
NEW!	CEMOTUSSO16W  Available in 2025	eMOTUSSO16	5" woofer and 1" tweeter (40 WRMS @ 16Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for low impedance(16Ω) audio lines. Includes a wall bracket and security steel cable. Dimensions (without accessories) 173x181x180mm. Weight 2.4 kg White colour. Price per unit, sold in pairs.	52,890 Ft	129 €
	CEMOTUS8ODBK 	eMOTUS8ODBK	8" woofer and 1" tweeter (100 WRMS @ 8Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for 70/100V (3,75/7,5/15/30W/60W) and low impedance(8Ω) audio lines. Includes a wall bracket and security steel cable. Dimensions (without accessories) 268x242x264mm. Weight 4.25 kg Black colour. Price per unit, sold in pairs.	115,620 Ft	282 €
	CEMOTUS8ODWH 	eMOTUS8ODWH	8" woofer and 1" tweeter (100 WRMS @ 8Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for 70/100V (3,75/7,5/15/30W/60W) and low impedance(8Ω) audio lines. Includes a wall bracket and security steel cable. Dimensions (without accessories) 268x242x264mm. Weight 4.25 kg White colour. Price per unit, sold in pairs.	115,620 Ft	282 €
	CEUC106BK 	eUC106BK	Spherical pendant loudspeaker featuring a 6,5" woofer, 0,5" tweeter. 40 WRMS @ 8Ω and 70/100V transformer.(32/ 16/ 8/ 4 W @ 100V). Dimensions (without accessories) ø270 x 215 (H). Weight 3 kg Stripped wire connection (3m). Black colour.	58,220 Ft	142 €
	CEUC106 	eUC106WH	Spherical pendant loudspeaker featuring a 6,5" woofer, 0,5" tweeter. 40 WRMS @ 8Ω and 70/100V transformer.(32/ 16/ 8/ 4 W @ 100V). Dimensions (without accessories) ø270 x 215 (H). Weight 3 kg Stripped wire connection (3m). White colour.	58,220 Ft	142 €

CECMP8	eCMP8	150W high efficiency musical projector ready for outdoor applications due to its waterproof and sun screening building material (IP56). It performs an 8" LF driver and 1,4" HF coaxial driver, 150W @ 8Ω nominal power and 70/100V line transformer with 37, 5/75/150W/ 8Ω power options. Dimensions: WxHxD: 300 x 302 x 334mm / 11.8" x 11.9" x 13.2" Weight: 11,0 kg / 24.3 lb	174,660 Ft	426 €
---------------	-----------------------	---	-------------------	--------------



CECMP12	eCMP12	300W high efficiency musical projector ready for outdoor applications due to its waterproof and sun screening building material (IP56). It performs an 12" LF driver and 1,7" HF coaxial driver, 300W @ 8Ω nominal power and 70/100V line transformer with 50/100/200W/8Ω power options. Dimensions: WxHxD: 407 x 410 x 378mm / 16.0" x 16.1" x 14.9" Weight: 20,0 kg / 44.1 lb	280,850 Ft	685 €
----------------	------------------------	---	-------------------	--------------



SUBWOOFERS

Ref.	Name		Lista ár HUF	RRP €	
NEW!	CKICKSB18	KICK-SB18	As the first Ecler outdoor subwoofer, the new KICK-SB18 features 1x8" woofers perfectly positioned to maximize the low frequency response while reducing the vibrations on the acoustic enclosure. It delivers 350 WRMS at 8Ω ready to be wall-mounted with the included bracket or positioned vertically and horizontally when needed. Dimensions TBC. Weight TBC Black color.	286,590 Ft	699 €



Available in 2025

NEW!	CKICKSB28	KICK-SB28	As the first Ecler outdoor subwoofer, the new KICK-SB28 features 2x8" woofers perfectly positioned to maximize the low frequency response while reducing the vibrations on the acoustic enclosure. It delivers 700 WRMS at 4Ω ready to be wall-mounted with the included bracket or positioned vertically and horizontally when needed. Dimensions (WxHxD) 660 x 450 x 250 mm / 255,98 x 17,71 x 9,84 in. Weight 23Kg/50.7lb Black color.	512,090 Ft	1,249 €
-------------	------------------	------------------	--	-------------------	----------------



NEW!	CEGESB110P	EDGE-SB110P	Breaking the limits of powerful bass sound in a compact size EDGE subwoofer is perfectly designed for small available spaces like underneath restaurant seats or wall-mounted in a corner with the included bracket. This powered subwoofer of 178 mm deep incorporates a 10" driver, 50Hz to 150Hz variable low pass filter, phase inverter and an amplified power output of 150W. Black color. Dimensions (WxHxD) 635 x 400 x 178 mm / 23,62 x 15,74 x 7 in. Weight 11,25Kg & 24,8 lb	184,090 Ft	449 €
-------------	-------------------	--------------------	---	-------------------	--------------



Available in 2025

Ref.	Name	ARQISI SERIES	Lista ár HUF	RRP €
CARQISSB6TIB	ARQISSB6TIBK	Wooden wall-mount subwoofer reinforcement cabinet, featuring a 6,5" driver and a passive 6,5" radiator. 480W peak power, 120 WRMS power @ 8 ohm and integrated 70/100V line transformer with 60 and 120W taps. Internal LPF with OFF, 120HZ and 150 HZ cut-off frequency selections. Installation U-bracket included. Dimensions (WxHxD) 250x390x130mm / 9.84"x15.35"x5.12". Weight 8,2 kg / 18.07 lb Black color.	217,300 Ft	530 €





CARQISSB6TIW	ARQISSB6TIWH	Wooden wall-mount subwoofer reinforcement cabinet, featuring a 6,5" driver and a passive 6,5" radiator. 480W peak power, 120 WRMS power @ 8 ohm and integrated 70/100V line transformer with 60 and 120W taps. Internal LPF with OFF, 120HZ and 150 HZ cut-off frequency selections. Installation U-bracket included. Dimensions (WxHxD) 250x390x130mm / 9.84"x15.35"x5.12". Weight 8,2 kg / 18.07 lb White color.	217,300 Ft	530 €
---------------------	------------------------------	---	-------------------	--------------





CARQISSB10IB	ARQIS SB10IBK	Wooden wall-mount subwoofer reinforcement cabinet with a slim and compact format and long term reliability, featuring a 10" driver (150 WRMS @ 8 ohm, 600W peak power) and internal LPF (OFF/ 120Hz/150Hz). Euroblock connector, wall mount and 12 x M8 rigging points included. Dimensions (WxHxD) 600x442x228mm / 23.62"x17.40"x8.97". Weight 16,6 kg / 36.37 lb. Black color.	221,810 Ft	541 €
---------------------	-------------------------------	---	-------------------	--------------





CARQISSB10IW	ARQIS SB10IWH	Wooden wall-mount subwoofer reinforcement cabinet with a slim and compact format and long term reliability, featuring a 10" driver (150 WRMS @ 8 ohm, 600W peak power) and internal LPF (OFF/ 120Hz/150Hz). Euroblock connector, wall mount and 12 x M8 rigging points included. Dimensions (WxHxD) 600x442x228mm / 23.62"x17.40"x8.97". Weight 16,6 kg / 36.37 lb. White color.	221,810 Ft	541 €
				

CARQISSB12IB	ARQIS SB12IBK	Wooden sub-woofer reinforcement cabinet with a compact format and long term reliability, featuring 300 WRMS @ 8 Ω and a 12" LF driver. 1200W Peak power. Double INPUT/STACK connector, Speakon® type. 8 x M8 rigging points included. Dimensions (WxHxD) 445 x 445 x 375 mm / 17.51 x 17.51 x 14.76 in. Weight 23 kg / 50,70 lb. Available only in black color.	296,430 Ft	723 €
				

CARQISSB15IB	ARQIS SB15IBK	Wooden sub-woofer reinforcement cabinet with a compact format and long term reliability, featuring 600 WRMS @ 8 Ω and a 15" LF driver. 2400W Peak power. Double INPUT/STACK connector, Speakon® type. 35 mm top-hat pole mount socket and 8 x M8 rigging points included. Dimensions (WxHxD) 534 x 525 x 460 mm / 21.02 x 20.67 x 18.11 in. Weight 32 kg / 70,54 lb. Available only in black color.	375,150 Ft	915 €
				

Ref.	Name		Lista ár HUF	RRP €
CTRAILS6TBK	TRAILS6TBK	Wooden subwoofer reinforcement cabinet with a very compact format, featuring a 6,5" driver, 60 WRMS @ 8Ω, 70/100V line transformer (7.5/15/30/60 W), and internal Low Pass Filter(150Hz / OFF). Specifically designed to fulfil permanent installation requirements: concealed in false ceilings or partition walls, on walls' surface, etc. Installation accessories included. Dimensions 200x200x320 mm. Weight 6,3kg Available only in black finish. Delivered by units. Price per unit.	182,040 Ft	444 €
				

Ref.	Name	LABI SERIES	Lista ár HUF	RRP €
CLABI1SB18	LABI-SB18	LABI1-SB18 is an 18" passive subwoofer, 500W AES 8Ω, designed for fixed installations and portable applications (external amplification required). A stand alone compact subwoofer or combined with LABI1-C100i to create a complete powerful solution, easy to mount and plug and play. Dimensions: 513 x 513 x 704 mm / 20.2" x 20.2" x 27.7". Weight: 37kg / 81.8 lb.	641,240 Ft	1,564 €
				

CLABI1SB18P	LABI-SB18p	LABI1-SB18p is an 18" powered subwoofer, designed for fixed installations and portable applications. A stand alone compact subwoofer or combined with LABI1-C100i to create a complete solution. It performs 2400W Class D built-in amplification power: 1 x 1200W for its low frequency woofer, and 2x600W amplifiers, able to power up to 4 x LABI1-C100i. It also features DC protection to avoid damage to the loudspeakers, and performs 18 factory presets - selectable through the LCD screen. Dimensions: 513 x 513 x 704 mm / 20.2" x 20.2" x 27.7". Weight: 37kg / 81.8 lb.	1,295,600 Ft	3,160 €
				


Ref.	Name	LABI PACKS	Lista ár HUF	RRP €
CLABI1PACK1	LABI1PACK1 2 x LABI1-SB18p 4 x LABI1-C100i 2 x LABI1-SAC 2 x LABI1-CAC 2 x LABI1-SPC 2 x LABI1-CFC 2 x LABI1-SWK		5,849,880 Ft	14,268 €


CLABI1PACK2	LABI1PACK2 1 x LABI1-SB18p 2 x LABI1-C100i 1 x LABI1-SAC 1 x LABI1-CAC 1 x LABI1-SPC 1 x LABI1-CFC 1 x LABI1-SWK		2,924,940 Ft	7,134 €
--------------------	--	--	---------------------	----------------


CLABI1PACK3	LABIPACK3 2 x LABI1-SB18p 4 x LABI1-C100i 2 x LABI1-SAC 2 x LABI1-CAC		4,844,560 Ft	11,816 €
--------------------	--	--	---------------------	-----------------


CLABI1PACK4	LABIPACK4 2 x LABI1-SB18p 2 x LABI1-C100i 2 x LABI1-SAC		3,639,570 Ft	8,877 €
--------------------	---	--	---------------------	----------------


INDUSTRIAL LOUDPEAKERS


Ref.	Name		Lista ár HUF	RRP €	
CERK10R	eRK108		Outdoor and cost-effective ground loudspeaker. It features a 8" woofer, 0.5" tweeter. 70/100V transformer (15W). IP65 rated. Ready to be installed in gardens, theme parks, leisure facilities, etc. Dimensions 325x290x270mm. Weight 5kg	68,880 Ft	168 €

Ref.	Name		Lista ár HUF	RRP €	
CECS803	eCS803		Column loudspeaker, featuring 8 x 3" woofer transducers, 100 WRMS @ 8Ω, low impedance direct connection and 70/100V transformer (Selector de potencia: 30/ 20/ 10/ 5 W 100V/ 8 Ω). Aluminium enclosure with included wall bracket and IP44 outdoor class. Dimensions (without accessories) 105x760x90mm. Weight 4.5 kg	65,190 Ft	159 €

REF.	Name		Lista ár HUF	RRP €	
CEPRS10TI	ePRS10TI		10 WRMS sound projector carefully selected for the most extended 70/100V paging and background music applications. Manufactured in reinforced ABS and IP55 rated, therefore suitable for outdoor superior performance in music high-quality applications. Power selection: 2,5/5/10W @ 100V. Dimensions Ø 138 x 205mm. Weight 1.6kg (including accessories).	31,570 Ft	77 €





CEPRS20TI	ePRS20TI		20 WRMS sound projector carefully selected for the most extended 70/100V paging and background music applications. Manufactured in reinforced ABS and IP55 rated, therefore suitable for outdoor superior performance in music high-quality applications. Power selection: 5/ 10/ 20W @ 100V. Dimensions Ø 170 x 245mm. Weight 1.8 kg (including accessories).	33,620 Ft	82 €
------------------	--------------------------	---	--	------------------	-------------

CEPHS30TI	ePHS30TI		30 WRMS horn loudspeaker carefully selected for the most extended 70/100V paging and background music applications, offering durability and optimal speech and music reproduction. Manufactured in reinforced ABS and IP66 rated, therefore suitable for outdoor superior performance. Power selection: 30W / 20W / 10W / 5W @ 100V. 30WRMS @ 8Ω. Dimensions Ø 246 x 292mm. Weight 2.4kg (including accessories).	42,640 Ft	104 €
------------------	--------------------------	---	---	------------------	--------------





CEMSP50TI	eMSP50TI		50 WRMS 2-way musical horn carefully selected for the most extended 70/100V paging and background music applications, offering durability and optimal speech and music reproduction. Manufactured in reinforced ABS and IP66 rated, therefore suitable for outdoor superior performance in music high-quality applications. Power selection: 2.6/4.5/9/12.5/25/50W @ 100V. 50WRMS @8Ω. Dimensions 362x252x310mm. Weight 3.9kg (including accessories).	88,150 Ft	215 €
------------------	--------------------------	---	--	------------------	--------------












REMOTE CONTROLS & INTERFACES













PAGING STATIONS












Ref.	Name	MPAGE SERIES	Lista ár HUF	RRP €
CPAGENETDN	PAGENETDN	Desktop paging console for voice notices with Dante™ audio over IP. Features a 10" touch screen, a server client and a UCP server (User Control Panel). Since it's a server/UCP client device, it's possible to add other kind of control panels beside the ones destined for voice messages such as: volume control, sound source selection, presets recovery, communication via TCP/UDP with external devices, etc. Power over Ethernet or local power supply. Gooseneck microphone included.	917,990 Ft	2,239 €
				
CMPAGE	eMPAGE	Digital paging station (MPAGE16's evolution), compatible with HUB, MIMO88, MIMO88SG and MIMO1212SG digital matrixes. Includes: a gooseneck cardioid microphone (removable); 16 zone-selection keys; ALL, CLEAR and PAGE keys; 2 programmable keys, F1 & F2, for zone-group selection. Text labelling for destination areas by means of programmable electronic ink display. Dimensions (microphone excluded) 150mm x 180mm x 50mm. Weight 900g.	247,230 Ft	603 €
				
CMPAGE1R	MPAGE1r	1-zone desktop paging station, compatible with any device including a phantom-powered microphone input (SAM series, COMPACT series, DAM614, MIMO88, CA series, HMA series, etc.). Internal connections for a secure wiring. Dimensions (microphone excluded) 120mm x 126mm x 43mm. Weight 625 g.	84,870 Ft	207 €
				
CMPAGE4	MPAGE4	4-zone desktop paging station compatible with DAM614, CA series, etc. It allows for real-time paging with zones' destination selection. Selectable chime melody. Dimensions (microphone excluded) 120mm x 126mm x 43mm. Weight 650 g.	137,350 Ft	335 €
				












DIGITAL CONTROLS & PANELS













Ref.	Name		Lista ár HUF	RRP €
NEW! CPULSO4	PULSO-4	PULSO-4 is a digital remote wall panel with an elegant minimalistic design. Featuring aluminum frame and capacitive 4" TFT 480x480 display, the new PULSO wall panels are the perfect choice to load the User Control Panels of VIDA Series, EclerNet and HUB Series. Single unit EU electrical wall box. PoE or external power supply.	Hamarosan	TBC
				
Available in 2025				
NEW! CPULSO6	PULSO-6	PULSO-6 is a digital remote wall panel with an elegant minimalistic design. Featuring aluminum frame and capacitive 5,5" TFT 720x1280 display, the new PULSO wall panels are the perfect choice to load the User Control Panels of VIDA Series, EclerNet and HUB Series. Single unit EU electrical wall box. PoE or external power supply.	Hamarosan	TBC
				
Available in 2025				
NEW! CPULSO10	PULSO-10	PULSO-10 is a digital remote wall panel with an elegant minimalistic design. Featuring aluminum frame and capacitive 10" TFT 1280x 1800 display, the new PULSO wall panels are the perfect choice to load the User Control Panels of VIDA Series, EclerNet and HUB Series. Single unit EU electrical wall box. PoE or external power supply.	Hamarosan	TBC
				
Available in 2025				
Ref.	Name		Lista ár HUF	RRP €
CWPNETTOUCH	WPNETTOUCH	Remote control TFT touchscreen compatible with all EclerNet products such as: MIMO4040DN, MIMO88/SG, MIMO1212SG, NXA Series and DUO-NET PLAYER. Incorporates a capacitive 10" touch screen, a server client and UCP server (User Control Panel). When including a WPNETTOUCH in an EclerNet installation is not necessary to use a computer to manage connected devices, neither to have the UCP panels created for the project. Power over Ethernet or local power supply. Surface-mount accessories included. Compatible with VESA75 mounting standard. 260x178x28mm, 700gr.	436,240 Ft	1,064 €
				












CWP22DN 	WP22DN	Dante™ interface in a wall panel format. It features 2 audio MIC/LINE Combo connector inputs in its frontal panel and 2 Dante™ conversion channels either directly or by the sum of channels (stereo to mono conversion). Also, it features 2 analogue outputs with duplicated connectors in XLR format for the front panel and Euroblock on the rear panel, both linked to 2 Dante™ channels coming from the local network. PoE supply or local power supply.	305,860 Ft	746 €
CWPNET4KVR 	WPNET4KV	EclerNet compatible wall panel. It features a LCD screen, encoder and 4 selection keys. Works perfectly to enable volume control, source and preset selection functions. Ethernet interface. PoE or local power supply.	161,130 Ft	393 €
CWPNET8KR 	WPNET8K	EclerNet compatible wall panel. It features a LCD screen and 8 selection keys. Works perfectly to enable presets or source selection functions. Ethernet interface. PoE or local power supply.	161,130 Ft	393 €
CEMCONTROL1R 	eMCONTROL1	Digital control panel for the HUB matrix with a wall format, It makes it possible to act as a zone control, enabling the user to have 3 functions : volumen adjustment/MUTE, selection of musical sources and EQ adjustment with 3 band tone control. Coupled to a WPa type panel with an audio connector, provide remote control + balanced audio signal to the HUB, using only a single CAT5 type cable or higher. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	79,540 Ft	194 €
CEMCTROL1US 	eMCTROL1US	Digital control panel for the HUB matrix with a wall format with USA frame. It makes it possible to act as a zone control, enabling the user to have 3 functions : volumen adjustment/MUTE, selection of musical sources and EQ adjustment with 3 band tone control. Coupled to a WPa type panel with an audio connector, provide remote control + balanced audio signal to the HUB, using only a single CAT5 type cable or higher. Dimensions 116.5x114.8x27mm	79,540 Ft	194 €
ANALOGUE CONTROLS & PANELS				
Ref.	Name	WPa SERIES	Lista ár HUF	RRP €
CWPABT 	WPaBT	Class 1 bluetooth receiver (range 25m) A2DP profile, which keeps the standard wall-panel format of the WPa series. Include a Euroblock balanced stereo output, double-mono configurable. Easy device name, PIN, stereo / mono output configuration using the Ecler Bluetooth® Manager application for Windows devices. GPO available, useful for automatic priority management. Surface installation box included. Dimensions 86 x 38 x 86 mm.	98,810 Ft	241 €
CWPAMIXT 	WPaMIX-T	2 channel micro-mixer which keeps the standard wall-panel format of the WPm series. It allows to a mix a stereo unbalanced signal (2xRCA) with a microphone signal (XLR), getting a balanced mono output that can be sent to a preamplifier, amplifier, mixer, digital or analogue matrix, etc. The MIC input includes a 2 band EQ (BASS, TREBLE) and talk-over function. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	56,990 Ft	139 €
CWPAMIXTUS 	WPaMIX-TUS	2 channel micro-mixer which keeps the standard wall-panel format of the WPm series, but with USA frame. It allows to a mix a stereo unbalanced signal (2xRCA) with a microphone signal (XLR), getting a balanced mono output that can be sent to a preamplifier, amplifier, mixer, digital or analogue matrix, etc. The MIC input includes a 2 band EQ (BASS, TREBLE) and talk-over function. Dimensions 116.5x114.8x27mm	56,990 Ft	139 €
CWPAVOL 	WPaVOL	Remote wall panel control for one volume management. Compatible with all Ecler 0-10V DC REMOTE control port, like ALMA, MIMO88 / SG, NXA series, CA series, GPA series, etc. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	30,750 Ft	75 €
CWPAVOLUS 	WPaVOLUS	Remote wall panel control with USA frame for one volume management. Compatible with all Ecler 0-10V DC REMOTE control port, like MPA-R, ALMA, MIMO88 / SG, NXA series, CA series, GPA series, etc. Dimensions 116.5x114.8x27mm	35,670 Ft	87 €
CWPAVOLJ 	WPaVOL-J	Remote wall panel control for one volume management and a front panel stereo mini-jack connector. Compatible with all ECLER 0-10V DC REMOTE control port, like MPA-R, ALMA, MIMO88 / SG, NXA series, CA series, GPA series, etc.	36,080 Ft	88 €











	WPaVOL-SR	Remote wall panel control for one volume management + source or preset selection. Compatible with all Ecler 0-10V DC REMOTE control port, like MPA-R, ALMA, MIMO88 / SG, NXA series, CA series, GPA series, etc. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	43,870 Ft	107 €
	WPaVOL-SRUS	Remote wall panel control with USA frame for one volume management + source or preset selection. Compatible with all Ecler 0-10V DC REMOTE control port, like MPA-R, ALMA, MIMO88 / SG, NXA series, CA series, GPA series, etc. Dimensions 116.5x114.8x27mm	43,870 Ft	107 €
	WPaVOL-SR-J	Same features as WPaVOL-SR + front panel stereo mini-jack connector. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	45,920 Ft	112 €
	WPaCNX-CBO	Connection wall plate with Female 3 pin XLR connector + Jackk ST (combo connector). Screw-type connector at the back (no solder needed). Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	34,440 Ft	84 €
	WPaCNX-JRCA	Connection wall plate with 1 x stereo minijack and 2 x RCA connectors. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	32,390 Ft	79 €
	WPaH-AT6	70 / 100V line attenuator with integrated 24 VDC priority relay. 6W maximum output power. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	37,720 Ft	92 €
	WPaH-AT40	70 / 100V line attenuator with integrated 24 VDC priority relay. 40W maximum output power. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	45,100 Ft	110 €
	WPaH-AT100	70 / 100V line attenuator with integrated 24 VDC priority relay. 100W maximum output power. Universal surface-mount installation box included. Dimensions 172 x 38 x 86 mm.	48,380 Ft	118 €
	UBWPaVOL	UBWPaVOL is a remote wall panel control for one volume management, in US single gang bare format. It is compatible with Ecler devices including 0-10VDC or 0-12VDC remote control ports (internal jumper selectable). Dimensions: 35x65x35mm / 1.4"x2.5"x1.4". Weight: 30gr / 0.07 lb.	32,390 Ft	79 €
	UBWPaCNXJRC	UBWPaCNX-JRC is a connection wall-panel, in US single gang bare format, with 1 x stereo minijack and 2 x RCA connectors. This connector can be screwed at the rear (does not require any soldering). Dimensions: 35x65x35mm / 1.4"x2.5"x1.4". Weight: 30gr / 0.07 lb.	30,340 Ft	74 €
ACCESSORIES				
PRODUCT ACCESSORIES				
Ref.	Name		Lista ár HUF	RRP €
	ETH232AD	Ecler ETH232AD is a serial interface that allows bidirectional transparent transmission between RS-232/422/485 and Ethernet. It includes a setting webpage for Ethernet and Serial customized settings. Dimensions: 100 × 86 × 26 mm (3.94" × 3.39" × 1.02") Weight: 0.5kg / 1.10 lb.	87,740 Ft	214 €
	1UHRMKIT	Kit that enables a half-width x 1U height rack device to be mounted into a standard width rack cabinet.	11,070 Ft	27 €




	ZUHRMKIT	Kit that enables a half-width x 2U height rack device to be mounted into a standard width rack cabinet.	14,760 Ft	36 €
	VEORACK19	Universal 19" rack mount accessory. Mounting screws and Velcro® included.	40,590 Ft	99 €
	PUM3	Ecler PUM3 is a rack-mount accessory that allows to mount two half-width RU devices in 1 standard width RU space. Mounting screws included.	7,380 Ft	18 €
	WPa2FMBOX	Double Flush-Mount box, compatible with the WPa wall panel series. It includes a single frame for fitting 2 adjacent panels in a twin housing.	20,910 Ft	51 €
	WPa2SMBOX	Double Surface-mount box, compatible with the WPa wall panel series. It includes a single frame for fitting 2 adjacent panels in a twin housing.	20,910 Ft	51 €
	WP24-PSU	Ecler WP24-PSU is a 24VDC 0.5A external PSU. International AC plugs set. Coaxial connector (+ center), compatible with eMPAGE, DN44BOB, WPNET Series, eMCONTROL1, WPaMIX-T and WPaBT.	19,680 Ft	48 €
	LAB1-SWK	Subwoofer-Wheel-Kit. 4 wheel kit for LAB1-SB18/18p subwoofer	63,550 Ft	155 €
	LAB1-CFC	Column-Flight-Case. Flight case for 2 LAB1-C100i + wiring + mounting accessories	387,450 Ft	945 €
	LAB1-SPC	Subwoofer-Protection-Cover. Nylon protection cover for LAB1-SB18/18p subwoofer	78,310 Ft	191 €
AUDIO CABLES & OTHERS				
Ref.	Name			
	MBSTAND	Microphone floor boom stand.	22,960 Ft	56 €
	MDSTAND	Microphone desktop stand.	6,150 Ft	15 €

	CNXAC8RM	CNXAC8RM	8 x Schuko sockets rack mount AC strip + ON/OFF switch, 1 RU.	17,220 Ft	42 €
	CNXEBC1	CNXEBC1	Euroblock 3 pin to Euroblock 3 pin premade cable, 1 metre length.	8,610 Ft	21 €
	CNXEBC2M5	CNXEBC2M5	Euroblock 3 pin to Euroblock 3 pin premade cable, 2.5 metre length.	9,020 Ft	22 €
	CNXEBC4	CNXEBC4	Euroblock 3 pin to Euroblock 3 pin, 4 connectors premade link cable (amplifiers, preamps and mixers inputs link wire, to share the same audio signal).	8,610 Ft	21 €
	CNXBRCA1	CNXBRCA1	Double Euroblock 3 pin to double RCA male and female connection premade cable including RCA to Euroblock unbalancing, 1 metre length.	10,250 Ft	25 €
	CNXRCAEBAD	CNXRCAEBAD	Euroblock 3 pin to RCA MONO female adapter including RCA to Euroblock unbalancing.	7,790 Ft	19 €
	CNXMJXLR2	CNXMJXLR2	2m length minijack ST to mono XLR male. Includes an internal resistance for overload protection and a proper sum of the signals.	10,250 Ft	25 €
	CNXXLRFEB	CNXXLRFEB	Euroblock 3 pin to XLR female connection premade cable, 0.5 metre length.	6,970 Ft	17 €
	CNXXLRLR1	CNXXLRLR1	XLR male to XLR female cable, 1 metre length.	7,790 Ft	19 €
	CNXXLRLR5	CNXXLRLR5	XLR male to XLR female cable, 5 metre length.	14,350 Ft	35 €
	CNXXLRLR10	CNXXLRLR10	XLR male to XLR female cable, 10 metre length.	22,550 Ft	55 €
LOUDSPEAKERS HARDWARE					
NEW!	CFLATYBK	FLATY	FLATY is a wall bracket that allows the columns of the MIA series to be installed attached to the wall. It is made of stainless steel and allows the height to be adjusted at any point along the length of the column, as well as allowing 2 columns to be installed side by side on top of each other. Black color.	11,890 Ft	29 €

NEW!	CFLATYWH	FLATY	FLATY is a wall bracket that allows the columns of the MIA series to be installed attached to the wall. It is made of stainless steel and allows the height to be adjusted at any point along the length of the column, as well as allowing 2 columns to be installed side by side on top of each other. White color.	11,890 Ft	29 €
					
NEW!	CHANDYBK	HANDY	HANDY is a wall bracket compatible with the MIA and NIMBO-14 series. It is incredibly versatile and intelligent with swivel and tilt adjustment, made of stainless steel. Black color.	20,090 Ft	49 €
					
NEW!	CHANDYWH	HANDY	HANDY is a wall bracket compatible with the MIA and NIMBO-14 series. It is incredibly versatile and intelligent with swivel and tilt adjustment, made of stainless steel. White colour.	20,090 Ft	49 €
					
NEW!	CGROUNDYBK	GROUNDY	GROUNDY is a bracket that allows you to install eMOTUS series speakers on the floor. Compatible with eMOTUS3OD, eMOTUS5P, eMOTUS5PB and eMOTUS5OD. Available in black colour.	14,350 Ft	35 €
					
NEW!	CCEILYBK	CEILY	CEILY is a bracket that allows eMOTUS series speakers to be mounted on the ceiling. Compatible with eMOTUS3OD, eMOTUS5P, eMOTUS5PB and eMOTUS5OD. Black colour.	15,990 Ft	39 €
					
NEW!	CCEILYWH	CEILY	CEILY is a bracket that allows eMOTUS series speakers to be mounted on the ceiling. Compatible with eMOTUS3OD, eMOTUS5P, eMOTUS5PB and eMOTUS5OD. White colour.	15,990 Ft	39 €
					
CRAILAPTORWH	RAILAPTOR		RAILAPTOR is an adapter for hanging compatible loudspeakers from a ceiling light rail. It is suitable for eMOTUS5OD, AUDEO103 and AUDEO106 cabinets and light rails performing 4 wire 3 circuit track system such as Global Track Pro, Eutrac or other compatible systems. Dimensions: 85x150x30 mm / 3.3"x5.9"x1.2". Weight: 130gr / 0,29lb. White colour.	9,840 Ft	24 €
					
CRAILAPTORBK	RAILAPTOR		RAILAPTOR is an adapter for hanging compatible loudspeakers from a ceiling light rail. It is suitable for eMOTUS5OD, AUDEO103 and AUDEO106 cabinets and light rails performing 4 wire 3 circuit track system such as Global Track Pro, Eutrac or other compatible systems.	9,840 Ft	24 €
					
CARQ108UBBK	ARQ108UBBK		Optional U-BRACKET accessory kit available for the ARQS108i model. Black colour.	18,450 Ft	45 €
					
CARQ108UBWH	ARQ108UBWH		Optional U-BRACKET accessory kit available for the ARQS108i model. White colour.	18,450 Ft	45 €
					
CARQ110UBBK	ARQ110UBBK		Optional U-BRACKET accessory kit available for the ARQS110i model. Black colour.	22,550 Ft	55 €
					
CARQ110UBWH	ARQ110UBWH		Optional U-BRACKET accessory kit available for the ARQS110i model. White colour.	22,550 Ft	55 €
					

	CARQ112UBBK	ARQ112UBBK	Optional U-BRACKET accessory kit available for the ARQJS112i model. Black colour.	24,600 Ft	60 €
	CARQ112UBWH	ARQ112UBWH	Optional U-BRACKET accessory kit available for the ARQJS112i model. White colour.	24,600 Ft	60 €
	CARQSB10SATB	ARQSB10SATB	EOL Kit including 2 metal brackets, to convert an ARQJSSB10i subwoofer unit into a hanging cluster, combining the ARQJS SB10 unit and 4 x eAMBIT103 satellite loudspeakers. (loudspeakers not included with this reference)	36,900 Ft	90 €
	CAVICAN6L	AVICAN6L	EOL Low Profile Back Can for VIC6 in-ceiling loudspeakers. Delivered by master carton of 2 units. Price per unit.	15,580 Ft	38 €
	CAVICSG	AVICSG	Printable squared grill for VIC series (6 & 8 inches compatible). Magnetic fixation. White colour. Delivered by master carton of 2 units. Price per pair.	14,760 Ft	36 €
	CAVICRG6BK	AVICRG6	Printable round grill for VIC series (6 inches compatible). Magnetic fixation. Black colour. Delivered by master carton of 2 units. Price per pair.	13,940 Ft	34 €
	CAVICRG6WH	AVICRG6	Printable round grill for VIC series (6 inches compatible). Magnetic fixation. White colour. Delivered by master carton of 2 units. Price per pair.	13,940 Ft	34 €
	CAVICRG8BK	AVICRG8	Printable round grill for VIC series (8 inches compatible). Magnetic fixation. Black colour. Delivered by master carton of 2 units. Price per pair.	15,580 Ft	38 €
	CAVICRG8WH	AVICRG8	Printable round grill for VIC series (8 inches compatible). Magnetic fixation. White colour. Delivered by master carton of 2 units. Price per pair.	15,580 Ft	38 €
	CICTB6	IC-TB6	Tile bridge compatible with IC6 in-ceiling loudspeakers. Sold in kits of 2 units. Price per kit.	31,160 Ft	76 €
	CICTB8	IC-TB8	Tile bridge compatible with IC8 and IC6CLASS series in-ceiling loudspeakers. Sold in kits of 2 units. Price per kit.	33,620 Ft	82 €








	COLORPAINT	COLORPAINT	Launching of painting in ceiling loudspeakers grilles (PKIC6,PKIC8, AVICSG, AVICRG) in a RAL colour . There is no charge for launching when painting a minimum of 100 units in the same RAL colour.	97,990 Ft	239 €
	CPAINT15	PAINT15	Painting by unit when there are less than 10 units.	15,990 Ft	39 €
	CPAINT10S	PAINT10S	Painting by unit when there are more than 10 units and with a maximum of 99 units.	8,200 Ft	20 €
	CPAINT100S	PAINT100S	Painting by unit when there are 100 or more units.	5,740 Ft	14 €
	CPKIC6	PKIC6	Accessory for personalizing the IC6 ceiling loudspeaker. The kit includes a grille that can be painted (with the appearance of the IC6CLASS) and an accessory (anchor ring) to mount this grille on the IC6. Easy to paint and mount.	16,400 Ft	40 €
	CPKIC8	PKIC8	Accessory to personalize the IC8 ceiling loudspeaker. The kit includes a grille that can be painted (with the appearance of the IC6CLASS) and an accessory (anchor ring) to mount this grill on the IC8. Easy to paint and mount.	16,400 Ft	40 €
	CPOLE01	POLE01	Adjustable 35 mm rod for pole for loudspeaker mount on top of a sub-woofer unit (ARQIS110i on top of ARQISSB15).	17,220 Ft	42 €
	CSR12	SR12	Mount bracket for ARQIS110i and ARQIS112i loudspeakers. Delivered by master carton of 2 units. Price per unit.	14,760 Ft	36 €
	CTRIP01	TRIP01	Loudspeaker floor stand with 35 MM pole. Delivered by master carton of 2 units. Price per unit.	30,750 Ft	75 €
	CLAB1SAC	LAB1-SAC	Subwoofer-adaptor-column, to install the LAB11-C100i satellite loudspeaker on LAB11-SB18p	72,160 Ft	176 €
	CLAB1CAC	LAB1-CAC	Column-adaptor-column, to connect vertically two LAB11-C100i column loudspeakers. Includes 60cm Speakon®-Speakon® cable. Warning: Only for stacking, NOT for flying	86,100 Ft	210 €
	CLAB1TBC	LAB1-TBC	Truss-Bracket-Column. Support to install a LAB11-C100i loudspeaker to truss	52,070 Ft	127 €
	CLAB1PBC	LAB1-PBC	Pole-Bracket-Column. Pole adaptor to install LAB11-C100i loudspeakers in a 35mm standard pole	88,560 Ft	216 €

CLABI1WBC 	LABI1-WBC	Wall-Bracket-Column. LABI1-C100i wall mount bracket	58,630 Ft	143 €
CLABI1HBC 	LABI1-HBC	Horizontal-Bracket-Column. High-density foam pieces to let LABI1-C100i rest on the floor horizontally. Allows 0°/ 30°/ 45° inclinations relative to the horizontal surface	14,760 Ft	36 €
CLABI1ODCNX 	LABI1-ODCNX	Outdoor kit to cover LABI1-C100i connections and make it ready for outdoor applications	29,930 Ft	73 €


VIDEO

SWITCHERS


Ref	Name		Lista ár HUF	RRP €
CVEOSWC44 	VEO-SWC44	Wireless conferencing and presentation switcher with Full HD video resolution wireless inputs and a 4K / UHD HDMI 2.0 video output. It supports wireless connection for USB devices like webcam and mic via dongle, Windows & macOS applications and is also Airplay / Miracast compliant. An integrated audio de-embedder provides stereo unbalanced analogue output on a 3,5mm jack connector. Includes a WebGUI for configuration and management as well as RS-232,TCP/IP remote control, all enabled by a pair of LAN RJ-45 connectors with independent networks available. Support for PoE. Dimensions 41x220x120 mm / 1.6"x8.66"x4.72". Weight 1 kg / 2.2 lb.	387,450 Ft	945 €
CVEOSWC44TU 	VEO-SWC44TU	Plug-n-play USB Type-C for wireless connection with a laptop or PC.	120,950 Ft	295 €
CVEOSWC44TH 	VEO-SWC44TH	Plug-n-play HDMI for wireless connection with a laptop or PC.	120,950 Ft	295 €
CVEOSWM44 	VEO-SWM44	VEO-SWM44 is a compact 4K presentation switcher that includes 2 HDMI 2.0, a USB-C and Miracast/Airplay wireless input selection via VEOCast to a single HDMI 2.0 output, supporting resolutions up to 4K/60Hz 4:4:4 HDR10 and Dolby Vision. An integrated audio de-embedder provides stereo analogue balanced outputs on Euroblock connectors. VEO-SWM44 includes 2 USB 3.0 type B and 2 USB 3.0 type A in order to support soft codec applications and external devices like webcam and KVM kits. Input selection is available via Auto-switching function, front panel buttons or RS-232. Display control via front panel buttons through CEC or RS-232. Smart EDID management and HDCP 2.2 support. Dimensions (WxHxD) 220mm x 44mm x 150mm / 8.66" x 1.73" x 5.90" Weight 1,25 Kg / 2.75 lb	501,430 Ft	1,223 €
CVEOSWH44 	VEO-SWH44	4x1 HDMI switcher for high dynamic range (HDR) formats. It is HDCP 2.2 compliant and supports 4K/UHD video @ 60 Hz with 4:4:4 chroma sampling, as well as HDMI signals with bandwidth up to 18 Gbps. It is the ideal solution for applications requiring 4K/UHD and HDR sources and displays. VEO-SWH44 includes audio de-embedding features and audio EDID management. The HDMI selection could be automatic (sense selection) and manual (frontal panel, remote control or serial commands). The controls include ARC mute and LED indications of the selected sources and settings. Dimensions (WxHxD) 85 x 12 x 180 mm / 3.34" x 0.47" x 7.09" Weight 300g / 0.66 lb	91,840 Ft	224 €

MATRIXES				
Ref	Name		Lista ár HUF	RRP €
CVEOMXH44D	VEO-MXH44D	4x4 HDMI 2.0 matrix with support for up to 4K/UHD video resolution, 60 Hz and 4:4:4 chroma sampling. It includes 8 analogue and digital audio de-embedding outputs as well as EDID management, a LCD display and an integrated WebGUI that allows to configure and control the unit. VEO-MXH44D can load and launch up to 8 presets which makes it a very interesting solution for professional applications that require video and audio HDMI signals routing between 4K/UHD sources and displays with a smart control management. Control via front panel and display, IR remote, RS-232 control, IP control and WebGUI. Dimensions 34x216x128mm / 1,34"x8,50"x5,04". Weight 470g / 1,04 lb.	284,950 Ft	695 €
				
CVEOMXH88D	VEO-MXH88D	8x8 HDMI 2.0 matrix with support for up to 4K/UHD video resolution, 60 Hz and 4:4:4 chroma sampling. It includes 8 analogue audio inputs and 16 analogue and digital audio de-embedding outputs as well as EDID management, a LCD display and an integrated WebGUI that allows to configure and control the unit. VEO-MXH88D can load and launch up to 8 presets which makes it a very interesting solution for professional applications that require video and audio HDMI signals routing between 4K/UHD sources and displays with a smart control management. Control via front panel and display, IR remote, RS-232 control, IP control and WebGUI. Dimensions 44x482x220mm / 1,73"x18,97"x8,66". Weight 2800g / 6,17 lb.	797,450 Ft	1,945 €
				
NEW! CVEOMXH48T	VEO-MXH48T	VEO-MXH48T is a 8x8 HDBaseT and HDMI® matrix with support for up to 4K/UHD video resolution, 60 Hz and 4:4:4 chroma sampling. It includes 8 analogue audio inputs and 16 analogue and digital audio de-embedding outputs as well as EDID management, a LCD display and an integrated WebGUI that allows to configure and control the unit in a very user friendly way. The HDBaseT outputs can deliver 4K/UHD video up to 40m and Full HD video up to 70m as well as PoC power supply to HDBaseT compliant receivers. It includes a video downscaler and an independent audio matrix. Dimensions 482.6 x 88 x 394 mm / 19 x 3.46 x 15.51 in. Weight 8.3 Kg / 18.30 lb.	1,434,590 Ft	3,499 €
				
SPLITTERS				
			Lista ár HUF	RRP €
CVEOSPH48	VEO-SPH48	1x8 HDMI splitter for high dynamic range (HDR) formats. It is HDCP 2.2/1.4 compliant and supports 4K/UHD video @ 60 Hz with 4:4:4 chroma sampling, as well as HDMI signals with bandwidth up to 18 Gbps. It is the ideal solution for applications requiring 4K/UHD and HDR sources and displays. It includes EDID management features, front panel LED indicators for power and signal status. Dimensions (WxHxD) 248mm x 17mm x 110mm / 9.76" x 0.67" x 4.33" Weight 610g / 1.34 lb	151,700 Ft	370 €
				
CVEOSPH44	VEO-SPH44	1x4 HDMI splitter for high dynamic range (HDR) formats. It is HDCP 2.2/1.4 compliant and supports 4K/UHD video @ 60 Hz with 4:4:4 chroma sampling, as well as HDMI signals with bandwidth up to 18 Gbps. It is the ideal solution for applications requiring 4K/UHD and HDR sources and displays. It includes EDID management features, front panel LED indicators for power and signal status. Dimensions (WxHxD) 150mm x 17mm x 65mm / 5.9" x 0.67" x 2.56" Weight 245g / 0.54 lb	75,440 Ft	184 €
				
CVEOSPH42	VEO-SPH42	1x2 HDMI splitter for high dynamic range (HDR) formats. It is HDCP 2.2/1.4 compliant and supports 4K/UHD video @ 60 Hz with 4:4:4 chroma sampling, as well as HDMI signals with bandwidth up to 18 Gbps. It is the ideal solution for applications requiring 4K/UHD and HDR sources and displays. It includes EDID management features, front panel LED indicators for power and signal status. Dimensions (WxHxD) 94mm x 15mm x 61mm / 3.7" x 0.59" x 2.4" Weight 120g / 0.265 lb	57,810 Ft	141 €
				
VIDEO DISTRIBUTION OVER IP				
			Lista ár HUF	RRP €
CVEOXTI2L	VEO-XTI2L	VEO-XTI2L and VEO-XRI2L are low latency 4K HDMI extenders over IP. Suitable both for creation of AVoverIP matrixes in multipoint-to-multipoint configurations and for point-to-point extensions up to 120m via single Cat.5e/6 cable. They also provide optional fiber optic connection for extension of 4K signals up to 2Km. Additional features like analog and digital audio embedding and de-embedding, and videowall option make this product a very versatile solution for many applications. An intuitive user panel with LEDs display allows to select the stream channel just out of the box, without the need of connecting a PC. The extenders can be power supplied both via PoE or via the included external PSU. Web browser interface, PC tools and third party control protocol are available for advanced settings and advanced control. Dimensions (WxHxD) 170 x 26 x 109 mm / 6.69" x 1.02" x 4.29" Weight 470g / 1.04 lb	266,500 Ft	650 €
				

	<p>CVEOXRI2L VEO-XRI2L</p>	<p>VEO-XTI2L and VEO-XRI2L are low latency 4K HDMI extenders over IP. Suitable both for creation of AVoverIP matrices in multipoint-to-multipoint configurations and for point-to-point extensions up to 120m via single Cat.5e/6 cable. They also provide optional fiber optic connection for extension of 4K signals up to 2Km. Additional features like analog and digital audio embedding and de-embedding, and videowall option make this product a very versatile solution for many applications. An intuitive user panel with LEDs display allows to select the stream channel just out of the box, without the need of connecting a PC. The extenders can be power supplied both via PoE or via the included external PSU. Web browser interface, PC tools and third party control protocol are available for advanced settings and advanced control. Dimensions (WxHxD) 170 x 26 x 109 mm / 6.69" x 1.02" x 4.29" Weight 470g / 1.04 lb</p>	<p>295,200 Ft 720 €</p>	
	<p>CVEOXTI1CG2 VEO-XTI1CG2</p>	<p>VEO-XTI1CG2 transmitter and VEO-XRI1CG2 receiver are a H.265 / H.264 over IP set of extenders that allow for HDMI distribution over 1Gb Ethernet networks with up to 1080p@60Hz video support. Suitable for various applications which also require PoE, audio management, video wall compositing or RS-232 control, such as educational, commercial or corporate installations, where flexible and scalable AV systems are in need. Signal transmission distance up to 100m over Cat5e/6/7 cable. Support for audio embedding and extraction. Support for pass through and RS-232, TCP/IP, WebGUI management using VEO-XCTRLG2 controller module. Dimensions 21,5x95x120mm / 0,85"x3,74"x4,72". Weight 74g / 0,16 lb.</p>	<p>153,750 Ft 375 €</p>	
	<p>CVEOXRI1CG2 VEO-XRI1CG2</p>	<p>VEO-XTI1CG2 transmitter and VEO-XRI1CG2 receiver are a H.265 / H.264 over IP set of extenders that allow for HDMI distribution over 1Gb Ethernet networks with up to 1080p@60Hz video support. Suitable for various applications which also require PoE, audio management, video wall compositing or RS-232 control, such as educational, commercial or corporate installations, where flexible and scalable AV systems are in need. Signal transmission distance up to 100m over Cat5e/6/7 cable. Support for audio embedding and extraction. Support for PoE function. Support for pass through and RS-232, TCP/IP, WebGUI management using VEO-XCTRLG2 controller module. Dimensions 21,5x95x120mm / 0,85"x3,74"x4,72". Weight 74g / 0,16 lb.</p>	<p>153,750 Ft 375 €</p>	
	<p>CVEOXCTRLG2 VEO-XCTRLG2</p>	<p>Control module for and expanded management experience with in-built WEB configuration interface. Dimensions 204 x 21.5 x 98.5mm / 4.7 x 0.85 x 3.88 in. Weight 0.540 Kg / 1.19 lb</p>	<p>143,500 Ft 350 €</p>	
EXTENDERS				
HDBASET		Lista ár HUF	RRP €	
	<p>CVEOXPT44A VEO-XPT44A</p>	<p>VEO-XPT44A allows to extend a 4K video signal up to 40m or a Full HD signal up to 70m over a single Cat 5e/6 cable. It supports 4K video signals at 60Hz with 4:4:4 YUV chroma subsampling and HDR10. The transmitter includes a HDMI loop output for monitoring or daisy-chain connection. A stereo unbalanced output on Euroblock connector is available both, on the transmitter and the receiver, for easy integration. In addition, VEO-XPT44A includes bidirectional PoH feature so the transmitter can be powered by the receiver and vice versa. With a reduced form factor and the added features of RS-232 and bidirectional IR, this is the perfect solution for any applications where AV and control extensions are required. Dimensions 154,4mm x 78,3mm x 20mm / 6.08"x 3.08"x 0.79". Weight: 688g / 1.52lbs (Pair)</p>	<p>189,010 Ft 461 €</p>	
	<p>CVEOXTT44 VEO-XTT44</p>	<p>Ecler VEO-XTT44 is a professional HDBaseT Transmitter of High Dynamic Range (HDR) formats for HDMI 2.0 extension. The extenders support video signal resolution up to 4K/UHD at 60Hz with 4:4:4 chroma sampling and HDMI data rate up to 18Gbps. Upscale fullHD input to 4K. Bidirectional PoH (Power Over HDBaseT) A 4-pin DIP switch allows managing EDID with multiple and customizable options. Include audio de-embedding and ARC support, bi-directional IR and RS-232 pass-through. A video pattern generator is included for testing purposes during the installation. Dimensions (WxHxD) 140mm x 84mm x 20mm / 5.51" x 3.31" x 0.79" Weight 275g / 0,606 lb</p>	<p>130,790 Ft 319 €</p>	
	<p>CVEOXRT44 VEO-XRT44</p>	<p>Ecler VEO-XRT44 is a professional HDBaseT Receiver of High Dynamic Range (HDR) formats for HDMI 2.0 extension. The extenders support video signal resolution up to 4K/UHD at 60Hz with 4:4:4 chroma sampling and HDMI data rate up to 18Gbps. The scaler implemented in the TX allows to upscale fullHD input to 4K. Bidirectional PoH (Power Over HDBaseT) . A 4-pin DIP switch allows managing EDID with multiple and customizable options. The extenders include audio de-embedding and ARC support, bi-directional IR and RS-232 pass-through Dimensions (WxHxD) 140mm x 84mm x 20mm / 5.51" x 3.31" x 0.79" Weight 290g / 0,640 lb</p>	<p>130,790 Ft 319 €</p>	


	VEO-XWT44E	<p>Ecler VEO-XWT44 is a HDBaseT transmitter in European 2-gang wallplate format. It allows to extend one 4K video signal up to 40m over a single Cat 5e/6 cable or a FullHD signal up to 70m when connected to VEO-XRT44. It supports real 4K video signals at 60Hz with 4:4:4 YUV chroma subsampling and HDR 10 with a maximum bandwidth of 18Gbps. With bidirectional PoC feature, the transmitter can be powered by the receiver and vice versa. VEO-XWT44 includes 2 HDMI 2.0 Inputs and one USB-C Input selectable via front panel button, automatic switching feature or RS-232. It allows extending IR and a bidirectional RS-232 signal along with the video signal. Dimensions(WxHxD) 146mm x 86mm x 42mm / 5.75" x 3.39" x 1.65". Weight 294g / 0.648 lbs</p>	309,550 Ft	755 €
---	----------------------------	---	-------------------	--------------


HDMI **Lista ár HUF** **RRP €**


	VEO-XPS43	<p>VEO-XPS43 is a professional HDMI extender kit that delivers 4K@30Hz up to 30m and a 1080p@60Hz up to 60m HDMI video extension over a single Cat. 6 cable or higher, with zero-latency, and 480i/480p/720p/1080i/1080p/UHD/4K resolution support. It includes unidirectional PoC (the receiver powered by the transmitter) and EDID management features as well as IR pass through, from the display to the source, for seamless integration. The transmitter also includes a HDMI loop output useful when integrating local displays and/or cascading to multiple devices. Dimensions 79.5mm x 69mm x 16.5mm (3.13"x2.71"x0.65") Weight TX: 132g / 0.291lbs, RX: 130g / 0.286 lbs</p>	59,450 Ft	145 €
---	---------------------------	--	------------------	--------------


AUDIO MANAGEMENT DEVICES

Lista ár HUF **RRP €**

	VEO-AXS4	<p>The VEO-AXS4 allows to extract audio signals from HDMI signals up to 4K. It provides a stereo analog output on RCA connectors or a 5.1 digital output on Toslink connector, selectable through the onboard switch. Dimensions (WxHxD) 105mm x 29mm x 65mm / 4.13" x 2.56" x 1.14" Weight 175g / 0.39 lb</p>	48,790 Ft	119 €
---	--------------------------	--	------------------	--------------


	VEO-AXS4P	<p>Ecler VEO-AXS4P is a professional HDMI audio extractor that allows to de-embed audio from a HDMI signal, including audio from 4K sources. VEO-AXS4P provides uncompressed LPCM analogue stereo signal through RCA and Phoenix balanced output as well as Dolby Digital and DTS multichannel signals through the coaxial S/PDIF digital output. VEO-AXS4P is HDCP 2.2 and HDMI 2.0 compliant, supporting data rates up to 18 Gbps and video resolutions up to 4K/60Hz with 4:4:4 chroma sample and HDR contents. Dimensions (WxHxD) 21.5 x 77 x 129 mm / 0.85" x 3.03" x 5.08" Weight 244 g / 0.538 lb</p>	61,090 Ft	149 €
---	---------------------------	--	------------------	--------------

	VEO-AEXS4	<p>VEO-AEXS4 allows to extract audio signals from HDMI streams up to 4K or to embed a stereo analogue signal into the HDMI, replacing the original sound. It provides a stereo unbalanced analogue input and output on Euroblock connectors, or a 5.1 digital output on S/PDIF coaxial connector. Function mode is selectable through the onboard dip-switch. Dimensions: 104.4 x 89 x 28.3mm (4.11 x 3.5x 1.11 inches). Weight: 155g / 0,342 lb</p>	52,890 Ft	129 €
---	---------------------------	--	------------------	--------------

	VEO-DACS4	<p>VEO-DACS4 allows to convert a digital audio signals from HDMI ARC inputs, S/PDIF Toslink or Coaxial, to a stereo analogue signal. In addition it can be used to convert digital S/PDIF audio from Toslink to Coaxial and vice versa. It provides a stereo balanced analogue output on Euroblock connectors, and RCA. Function mode is selectable through the onboard switch. Dimensions: 96.2 x 47.6 x 21mm (3.79 x 1.87 x 0.83 inches). Weight: 155 g (0.309 lbs)</p>	40,590 Ft	99 €
---	---------------------------	--	------------------	-------------


AV INTERFACES








Lista ár HUF **RRP €**

	VEO-CAP4U	<p>VEO-CAP4U is a plug-n-play HDMI to USB video capture device aimed for online media creators, schools, educational and corporate market etc. that require a professional solution for capturing and streaming their audiovisual content. This product is designed to easily record video and audio from an HDMI source, and send it to a PC / MAC over USB 3.0 without the need of an external power supply or installation drivers. A balanced line input automatically mixes an external sound source into the main audio stream. Dimensions: 102mm x 68mm x 12mm (4.02" x 2.68" x 0.59"). Weight: 75g / 0.165 lbs</p>	97,990 Ft	239 €
---	---------------------------	--	------------------	--------------

ACCESSORIES

Lista ár HUF **RRP €**

	VEO-RACK19	<p>Univ. 19" Rack mount shelf VEO series. Includes 12 x M3 screws with nuts and Dual Lock™ tape for devices not provided of mounting ears. Central holes for cable ties.</p>	40,590 Ft	99 €
---	----------------------------	--	------------------	-------------

	CVEOCH200	VEO-CH200	VEO-CH200 is a high speed HDMI 2.0 cable with Ethernet. These high quality cables are the perfect solution for professional installations, ensuring reliable and seamless HDMI 2.0 connections up to 18Gbps. All cables support HDMI, Ethernet, Audio and Control (ARC and CEC) signals. Length: 0.5m	2,870 Ft	7 €
	CVEOCH201	VEO-CH201	VEO-CH201 is a high speed HDMI 2.0 cable with Ethernet. These high quality cables are the perfect solution for professional installations, ensuring reliable and seamless HDMI 2.0 connections up to 18Gbps. All cables support HDMI, Ethernet, Audio and Control (ARC and CEC) signals. Length: 1m	3,690 Ft	9 €
	CVEOCH202	VEO-CH202	VEO-CH202 is a high speed HDMI 2.0 cable with Ethernet. These high quality cables are the perfect solution for professional installations, ensuring reliable and seamless HDMI 2.0 connections up to 18Gbps. All cables support HDMI, Ethernet, Audio and Control (ARC and CEC) signals. Length: 2m	4,920 Ft	12 €
NEW! 	CVEOCH203	VEO-CH203	VEO-CH203 is a high speed HDMI 2.0 cable with Ethernet. These high quality cables are the perfect solution for professional installations, ensuring reliable and seamless HDMI 2.0 connections up to 18Gbps. All cables support HDMI, Ethernet, Audio and Control (ARC and CEC) signals. Length: 3m	6,560 Ft	16 €
	CVEOCH205	VEO-CH205	VEO-CH205 is a high speed HDMI 2.0 cable with Ethernet. These high quality cables are the perfect solution for professional installations, ensuring reliable and seamless HDMI 2.0 connections up to 18Gbps. All cables support HDMI, Ethernet, Audio and Control (ARC and CEC) signals. Length: 5m	8,200 Ft	20 €
NEW! 	CVEOCH208	VEO-CH208	VEO-CH208 is a high speed HDMI 2.0 cable with Ethernet. These high quality cables are the perfect solution for professional installations, ensuring reliable and seamless HDMI 2.0 connections up to 18Gbps. All cables support HDMI, Ethernet, Audio and Control (ARC and CEC) signals. Length: 8m	14,350 Ft	35 €
	CVEOCH210	VEO-CH210	VEO-CH210 is a high speed HDMI 2.0 cable with Ethernet. These high quality cables are the perfect solution for professional installations, ensuring reliable and seamless HDMI 2.0 connections up to 18Gbps. All cables support HDMI, Ethernet, Audio and Control (ARC and CEC) signals. Length: 10m	21,730 Ft	53 €
